

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
GPS RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97. 33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: RW30
WRING WP (IAF) *	8.00 ATD TO DUCOR WP	328.48/9.28	4500	CLIMBING LEFT TURN TO 3100 DIRECT TTE VOR/DME AND HOLD.
8.00 ATD TO DUCOR WP	DUCOR WP	328.48/8.00	3000	
EHF VORTAC (IAF) *	DUCOR WP	003.00/19.22	3000	ADDITIONAL FLIGHT DATA: HOLD NW, RT, 144.00 INBOUND FAS OBST: 649 TREE 355819/1190003 CHART: 655 TREE 355717/1190120 CHART: PORTERVILLE MOA CHART: BAKERSFIELD MOA
DUCOR WP	ISADY WP	337.26/9.84	2100	

1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. PROFILE STARTS AT DUCOR WP
3. FAC 314.03 FAF ISADY WP DIST FAF TO MAP THLD 5.00
4. MIN. ALT DUCOR WP 3000, ISADY WP 2100
8. MSA FROM: RW30 11400

MAG VAR: 15 E EPOCH YEAR: 80

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15 FOR THIS AIRPORT							ALTERNATE:	N A	X			
CATEGORY	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-30	900	1	458	900	1	458	900	1 1/4	458	900	1 1/2	458			
CIRCLING	900	1	458	900	1	458	900	1 1/2	458	1000	2	558			

NOTES:

- * ARM APPROACH MODE PRIOR TO IAF.

CITY AND STATE	ELEVATION: 442 TDZE: 442	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT N. / EFFECTIVE DATE:	SUP
PORTERVILLE, CA	AIRPORT NAME: PORTERVILLE MUNI	GPS	13 AUG 98 <i>TL 9846</i>	AMDT NONE
			GPS RWY 30, ORIG	DATED