

**Federal Aviation
Administration**

Transmittal Letter 16-11

April 8, 2016

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DAT	SUBJECT
26-May-16	SC	Aiken	Aiken Muni	6/4688	04/01/16	RNAV (GPS) RWY 7, Amdt 1B

AIRAC Date: 26 MAY 2016

FDC 6/4688 AIK IAP AIKEN MUNI, AIKEN, SC. RNAV (GPS) RWY 7, AMDT 1B...
CHANGE LOCAL ALTIMETER SETTING NOTE TO READ: WHEN LOCAL
ALTIMETER SETTING NOT RECEIVED, USE AUGUSTA RGNL AT BUSH FIELD
ALTIMETER SETTING: INCREASE LPV ALL CATS DA TO 819 FT, LNAV/VNAV ALL
CATS DA TO 890 FT, LPV ALL CATS VISIBILITY 1/4 MILE AND LNAV/VNAV ALL
CATS 3/8 MILE; INCREASE ALL MDA 120 FT AND LNAV CAT C/D VISIBILITY 3/8
MILE AND CIRCLING CAT D 1/4 MILE. THIS IS RNAV (GPS) RWY 7, AMDT 1C.
1602161837-PERM