

RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW05 CLIMB TO 4000 DIRECT YACUD AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 228.00 INBOUND. CHART FAS OBST: 1113 TREE 344728N/0824235W DISTANCE TO THLD FROM 250 HAT: 0.75 NM. CHART VDP AT 1.23 MILES TO RW05* *LNAV ONLY. WAAS CHANNEL # 99517 REFERENCE PATH ID: W05A											
WOKEP (IAF)	ZAKOB (NOPT) (FB)	137.77 / 5.00	3000												
HULNO (IAF)	ZAKOB (NOPT) (FB)	317.85 / 5.00	3000												
ZAKOB (IF/IAF)	CONOA (FB)	047.81 / 6.30	2200												
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD SW ZAKOB, RT, 047.81 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 047.86 FAF: CONOA DIST FAF TO MAP: 3.70 THLD: 3.70 4. MIN. ALT: ZAKOB 3000, CONOA 2200 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: 2200 GS ALT AT: CONOA 2200 OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: 3.00 TCH: 45.0 34:1 IS NOT CLEAR 8. MSA FROM: <u> </u>				MAG VAR: 4W EPOCH YEAR: 1995											
MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	X										
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1246	1	250	1246	1	250	1246	1	250	1246	1	250			
LNAV/VNAV DA	1441	1 3/4	445	1441	1 3/4	445	1441	1 3/4	445	1441	1 3/4	445			
LNAV MDA	1380	1	384	1380	1	384	1380	1	384	1380	1 1/4	384			
CIRCLING	1560	1	547	1560	1	547	1560	1 1/2	547	1660	2	647			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 46C (114F). CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT. SEE 8260-10															
CITY AND STATE			ELEVATION: 1013 TDZE: 996			FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP:			
PICKENS, SC			AIRPORT NAME:						RNAV (GPS) RWY 5, ORIG			AMDT: NONE			
			PICKENS COUNTY						03 JUN 2010			DATED			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CLEMSON ALTIMETER SETTING AND INCREASE LPV DA TO 1292, LNAV/VNAV DA TO 1487, AND ALL MDA 60 FEET; INCREASE LPV ALL CATS, LNAV AND CIRCLING CATS C AND D VISIBILITY 1/4 MILE.

CHART NOTE: BARO-VNAV NA WHEN USING CLEMSON ALTIMETER SETTING.

CHART NOTE: VDP NA WITH CLEMSON ALTIMETER SETTING.

TAA

	FROM	TO	ALT
1.	318/30 CW 060/30 (NOPT)	ZAKOB (IF/IAF) (FB)	3000
	060/12 CW 138/12	ZAKOB (IF/IAF) (FB)	3000
2.	060/30 CW 138/30 (NOPT)	060/12 CW 138/12	6500
3.	138/30 CW 228/30	138/11 CW 228/11	6800
4.	138/11 CW 228/11	WOKEP (IAF) (FB)	3700
5.	228/30 CW 318/30	HULNO (IAF) (FB)	3700

QUALITY
CHECKED

CITY AND STATE

PICKENS, SC

ELEVATION: 1013

TDZE: 996

AIRPORT NAME:

PICKENS COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 5, ORIG

03 JUN 2010

SUP:

AMDT: NONE

DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KLQK
RUNWAY	RW05
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W05A
LTP/FTP LATITUDE	344818.0785N
LTP/FTP LONGITUDE	0824231.1565W
LTP/FTP ELLIPSOIDAL HEIGHT	+02627
FPAP LATITUDE	344922.3900N
FPAP LONGITUDE	0824116.1300W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

C2768B3A

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+02937
FPAP ORTHOMETRIC HEIGHT	+02937

CITY AND STATE
PICKENS, SC

ELEVATION: 1013 TDZE: 996
AIRPORT NAME:
PICKENS COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 5, ORIG
03 JUN 2010

SUP:
AMDT: NONE
DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

QUALITY
6
CHECKED

CITY AND STATE PICKENS, SC	ELEVATION: 1013 TDZE: 996 AIRPORT NAME: PICKENS COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 5, ORIG 03 JUN 2010	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	6	7	8	9	0	1	2	3
PP	1234567890123456789012345678901234567890123456789012345678901234567890123456789012												

	SUSAP KLQKK7PR05	RW05 002E	+02937+02937LPV		99517								

QUALITY
6
CHECKED

CITY AND STATE
PICKENS, SC

ELEVATION: 1013 TDZE: 996
AIRPORT NAME:
PICKENS COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 5, ORIG
03 JUN 2010

SUP:
AMDT: NONE
DATED: