

**Federal Aviation
Administration**

Transmittal Letter 21-18

JULY 9, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
8/12/2021	OH	Wooster	Wayne County	1/6033	6/25/2021	RNAV (GPS) RWY 28, Orig-B

AIRAC Date: 12 AUGUST 2021

FDC 1/6033 BJJ IAP WAYNE COUNTY, WOOSTER, OH. RNAV (GPS) RWY 28, ORIG-B...
CIRCLING CAT B MDA 1700/HAA 564, CAT C MDA 1800/HAA 664, CAT D MDA 1840/HAA
704. VIS CAT C 1 3/4, CAT D 2 1/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER
SETTING NOT RECEIVED, USE AKRON-CANTON RGNL ALTIMETER SETTING: INCREASE
LPV DA TO 1458 FEET, LNAV/VNAV DA TO 1649 FEET, AND VISIBILITY LPV ALL CATS 1/4
SM AND LNAV/VNAV ALL CATS 1/8 SM; INCREASE ALL MDA 60 FEET AND VISIBILITY LNAV
CAT C/D 1/8 SM AND CIRCLING CAT C/D 1/4 SM. ALTERNATE MINIMUMS: STANDARD
EXCEPT CAT D 800-2 1/4; NA WHEN LOCAL WEATHER NOT AVAILABLE. CHART PROFILE
NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH
{FEET}). THIS IS RNAV (GPS) RWY 28, ORIG-C. 2106171820-PERM