

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW22 CLIMB TO 600 THEN CLIMBING RIGHT TURN TO 2000 DIRECT TUBER AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 017.00 INBOUND. CHART FAS OBST: 218 TOWER 392853N/0743256W 260 AAO 392853N/0743256W CHART: ASR. CHART R-5002A, R-5002B, R-5002C. CHART W-107C. DISTANCE TO THLD FROM 296 HATH: 0.77 NM. CHART VDP AT 1.26 NM TO RW22* *LNAV ONLY. WAAS CHANNEL # 53631 REFERENCE PATH ID: W22A LTP HAE: -13.4 M									
VCN VOR/DME		PIDVE (TF) (FB) (RNP 2.00)			076.98 / 16.79			1800											
PIDVE (IAF)		KOPCE (TF) (FB) (RNP 1.00)			122.96 / 6.00			1800											
KOPCE (IF)		FLDER (TF) (FB) (RNP 1.00)			203.04 / 3.90			1600											
FLDER		EFEWY (TF) (FB) (RNP 1.00)			203.03 / 2.10			1100											
EFEWY (FAF)		RW22 (MAP) (TF) (FO) (RNP 0.30)			218.02 / 3.08														
(SEE FORM 8260-10)																			
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT KOPCE 3. FAC: 218.02 FAF: EFEWY DIST FAF TO MAP: 3.08 THLD: 3.08 4. MIN. ALT: KOPCE 1800, FLDER 1600, EFEWY 1100 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 1100 GS ALT AT: EFEWY 1100 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 51.0 34:1 IS NOT CLEAR 8. MSA FROM: RW22 2100																MAG VAR: 10W		EPOCH YEAR: 1965	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @										
CATEGORY =====>		A			B			C			D			E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LPV DA	364	1	296	364	1	296	364	1	296	364	1	296	364	1	296				
LNAV/VNAV DA	356	7/8	288	356	7/8	288	356	7/8	288	356	7/8	288	356	7/8	288				
LNAV MDA	520	1	452	520	1	452	520	1 1/8	452	520	1 1/8	452	520	1 1/8	452				
CIRCLING	540	1	465	540	1	465	540	1 1/2	465	640	2	565	760	2 1/2	685				
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -14C (7F) OR ABOVE 54C (130F). @ CAT E 800-2 1/2 CHART NOTE: RWY 22 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON VCN VORTAC AIRWAY RADIALS 066 CW 160. CHART PLANVIEW NOTE: RADAR REQUIRED, WHEN R-5002B IS ACTIVE.																			
CITY AND STATE		ELEVATION: 75 TDZE: 68			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:					SUP:							
ATLANTIC CITY, NJ		AIRPORT NAME:			ATLANTIC CITY INTL		RNAV (GPS) RWY 22, AMDT 4B					AMDT: 4A							
							12 OCTOBER 2017					DATED 05/29/2014							



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HATh, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW22 (MAP)	600 MSL (CA)	218.02	600
600 MSL	TUBER (DF) (FO) (RNP 1.00)		2000

QUALITY
16
CHECKED

CITY AND STATE
ATLANTIC CITY, NJ

ELEVATION: 75 TDZE: 68
AIRPORT NAME:
ATLANTIC CITY INTL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 22, AMDT 4B
12 OCTOBER 2017

SUP:
AMDT: 4A
DATED: 05/29/2014

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HATh, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KACY
RUNWAY	RW22
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W22A
LTP/FTP LATITUDE	392752.6715N
LTP/FTP LONGITUDE	0743429.8085W
LTP/FTP ELLIPSOIDAL HEIGHT	-00134
FPAP LATITUDE	392633.9300N
FPAP LONGITUDE	0743523.8100W
THRESHOLD CROSSING HEIGHT (TCH)	00051.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0880
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 DF24F2DD

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K6
LTP ORTHOMETRIC HEIGHT	+00205
FPAP ORTHOMETRIC HEIGHT	+00205

QUALITY
16
CHECKED

CITY AND STATE ATLANTIC CITY, NJ	ELEVATION: 75 TDZE: 68 AIRPORT NAME: ATLANTIC CITY INTL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, AMDT 4B 12 OCTOBER 2017	SUP:
				AMDT: 4A
				DATED: 05/29/2014