

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
GUNNE (IAF)	CABDA (NOPT) (FB)	351.80 / 9.55	2600
ESSIE (IAF)	CABDA (NOPT) (FB)	114.38 / 5.52	2600
CABDA (IF/IAF)	DIRKE (FB)	064.81 / 5.20	2600

LPV: DA
LNAV/VNAV: DA
LNAV: RW07

CUMB TO 3000 DIRECT LEBJE AND HOLD.

ADDITIONAL FLIGHT DATA:
HOLD NE, RT, 245.10 INBOUND.
CHART FAS DBST: 1079 TOWER 403600N/0830427W
CHART FAS DBST: 1135 TOWER 403529N/0830520W
CHART 1459 TOWER 403609N/083080W.
WAAS CHANNEL # 93604
REFERENCE PATH ID: W07A
DISTANCE TO THLD FROM 250 HAT: 0.66 NM

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD SW CABDA, RT, 064.81 INBOUND, 2600 FT. IN LIEU OF PT (IAF)
- FAC: 064.89 FAF: DIRKE DIST FAF TO MAP: 4.86 THLD: 4.86
- MIN. ALT: CABDA 2600, DIRKE 2600, ZULGA/2.50 NM TO RW07 1820*
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: 2600 GS ALT AT: DIRKE OM: MM: IM:
- GS ANGLE: 3.00 TCH: 40.0 34:1 IS NOT CLEAR
- MSA FROM: RW07 3100

MAG VAR: 5W EPOCH YEAR: 1985

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N/A	STANDARD @											
CATEGORY	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/H	
LPV DA	1240	1	250	1240	1	250	1240	1	250	1240	1	250				
LNAV/VNAV DA	1379	1 1/2	389	1379	1 1/2	389	1379	1 1/2	389	1379	1 1/2	389				
LNAV MDA	1440	1	450	1440	1	450	1440	1 1/4	450	1440	1 1/2	450				
CIRCLING	1480	1	487	1500	1	507	1540	1 1/2	547	1560	2	567				

NOTES:
CHART NOTE: BARO-VNAV NA WHEN USING OHIO STATE UNIVERSITY ALTIMETER SETTING.
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 46C (114F).
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
SEE 8260-10

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE MARION, OH	ELEVATION: 993 TDZE: 990 AIRPORT NAME: MARION MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO.: RNAV (GPS) RWY 7, ORIG AUG 30 2007	SUP: AMDT: NONE DATED
-------------------------------------	---	-------------------------------------	--	-----------------------------

TL 07-15