

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97. 23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		MAP: MVE R-148/15.06						
MVE VOR/DME		MELLL / 20.00 DME			148.21 / 20.00			3000		CLIMB TO 3000, THEN LEFT TURN VIA R-148 TO MELLL/ MVE 20 DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 328 INBOUND FAS OBST: 1189' TREE 444220 / 953109						
RWF VORTAC (IAF)		SOCSI / 25.00 DME (NoPT)			293.26 / 15.92			3000								
SOCSI		MELLL			328.21 / 5.00			3000								
1. PT <u>L</u> SIDE OF COURSE <u>148.21</u> OUTBOUND <u>3000</u> FT WITHIN <u>10</u> MILES OF <u>MELLL</u> (IAF) 2. _____ 3. FAC <u>328.21</u> FAF <u>MELLL</u> DIST FAF TO MAP _____ THLD <u>4.94</u> 4. MIN. ALT <u>MELLL 3000</u> 8. MSA FROM: <u>MVE VOR/DME 360-270 2600, 270-360 3400</u>										MAG VAR: 5E				EPOCH YEAR: 95		
MINIMUMS																
TAKEOFF: ☒ STANDARD		SEE FAA FORM 8260-15 FOR THIS AIRPORT						ALTERNATE: ☐ N ☒ X								
CATEGORY		A			B			C			D			E		
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-34		1480	1	435	1480	1	435	1480	1 1/4	435	1480	1 1/2	435			
CIRCLING		1520	1	473	1520	1	473	1520	1 1/2	473	1600	2	553			
NOTES: USE MONTEVIDEO ALTIMETER SETTING																
CITY AND STATE		ELEVATION: 1047 TDZE: 1045		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:						SUP				
GRANITE FALLS, MN		GRANITE FALLS MUNI		MVE		<u>72 98-26</u> 28 JAN 99 VOR/DME RWY 34, ORIG						AMDT NONE				
												DATED				