

RNAV - STANDARD US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION						INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.					
TERMINAL ROUTES												MISSED APPROACH									
FROM			TO			COURSE AND DISTANCE			ALTITUDE			LPV: DA LNAV/VNAV: DA LNAV: RW26 CLIMB TO 600, THEN CLIMBING LEFT TURN TO 7000 DIRECT NUTUW AND HOLD, CONTINUE CLIMB-IN-HOLD TO 7000. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 027.96 INBOUND. CHART FAS OBST: 182 BLD 594506N/1545306W. 250 AAO 594517N/1544529W DISTANCE TO THLD FROM 250 HAT: 0.77 NM. CHART VDP AT 0.82 NM TO RW26* *LNAV ONLY. WAAS CHANNEL # 45910 REFERENCE PATH ID: W26A CHART CIRCLING ICON. CHART NAKNEK 2 MOA LTP HAE: 56.4 M									
ULPIQ (IAF)			WAKNU (NOPT) (TF) (FB) (RNP 1.00)			348.94 / 10.00			6100												
FIVNO (IAF)			WAKNU (NOPT) (TF) (FB) (RNP 1.00)			168.97 / 10.00			6100												
WAKNU (IF/IAF)			JUSTM (TF) (FB) (RNP 1.00)			258.96 / 11.07			2800												
JUSTM (FAF)			WOKAD/4.15 NM TO RW26 (TF) (FB) (RNP 0.30)			258.64 / 4.08															
WOKAD/4.15 NM TO RW26			RW26 (MAP) (TF) (FO) (RNP 0.30)			258.64 / 4.15															
(SEE FORM 8260-10)																					
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD E WAKNU, LT, 258.96 INBOUND, 6100 FT. IN LIEU OF PT (IAF) 3. FAC: 258.64 FAF: JUSTM DIST FAF TO MAP: 8.23 THLD: 8.23 4. MIN. ALT: WAKNU 6100, JUSTM 2800, WOKAD/4.15 NM TO RW26 1500* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2800 GS ALT AT: JUSTM 2800 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 35.0 20:1 IS CLEAR 34:1 IS CLEAR 8. MSA FROM: _____																		MAG VAR: 14E		EPOCH YEAR: 2020	
MINIMUMS																					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @									
CATEGORY =====>		A			B			C			D			E							
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA						
LPV DA	424	1	250	424	1	250	424	1	250	424	1	250									
LNAV/VNAV DA	424	1	250	424	1	250	424	1	250	424	1	250									
LNAV MDA	440	1	266	440	1	266	440	1	266	440	1	266									
CIRCLING	740	1	548	740	1	548	800	1 3/4	608	1700	3	1508									
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -21C (-5F) OR ABOVE 54C (130F). @ CAT D 1600-3 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, PROCEDURE NA. CHART NOTE: DME/DME RNP-0.3 NA.																					
CITY AND STATE			ELEVATION: 192 TDZE: 174			FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP: RNAV (GPS) RWY 25									
ILIAMNA, AK			AIRPORT NAME: ILIAMNA						RNAV (GPS) RWY 26, AMDT 2			AMDT: 1									
									13 SEPTEMBER 2018			DATED 05/07/2009									



**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
RW26 (MAP)	600 MSL (CA)	258.64	600

600 MSL	NUTUW (DF) (FO) (RNP 1.00)	7000
---------	----------------------------	------

TAA

	<u>FROM</u>	<u>TO</u>	<u>ALT</u>
1.	169/30 CW 349/30 (NOPT)	169/4 CW 349/4	8100
2.	169/4 CW 349/4	WAKNU (IF/IAF) (FB)	6100
3.	349/30 CW 079/30	ULPIQ (IF/IAF) (FB)	6100
4.	079/30 CW 169/30	FIVNO (IAF) (FB)	6500

QUALITY
10
CHECKED

CITY AND STATE

ILIAMNA, AK

ELEVATION: 192

TDZE: 174

AIRPORT NAME:

ILIAMNA

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 26, AMDT 2

13 SEPTEMBER 2018

SUP: RNAV (GPS) RWY 25

AMDT: 1

DATED: 05/07/2009

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	PAIL
RUNWAY	RW26
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W26A
LTP/FTP LATITUDE	594504.6945N
LTP/FTP LONGITUDE	1545347.4340W
LTP/FTP ELLIPSOIDAL HEIGHT	+00564
FPAP LATITUDE	594508.4005N
FPAP LONGITUDE	1545643.3965W
THRESHOLD CROSSING HEIGHT (TCH)	00035.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1200
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

91E166DF

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	PA
LTP ORTHOMETRIC HEIGHT	+00440
FPAP ORTHOMETRIC HEIGHT	+00440

QUALITY
10
CHECKED

CITY AND STATE

ILIAMNA, AK

ELEVATION: 192

TDZE: 174

AIRPORT NAME:

ILIAMNA

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 26, AMDT 2

13 SEPTEMBER 2018

SUP:

RNAV (GPS) RWY 25

AMDT:

1

DATED:

05/07/2009