

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
OLAKE	ONE	OLAKE1.OLAKE	NONE		<i>12 AUG 2021</i>
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	☐	☐	☒	☐	☒

DP ROUTE DESCRIPTION:

TAKEOFF RWY 10L: CLIMB ON HEADING 098.78 TO 520, THEN DIRECT TO CROSS CRRMN AT OR ABOVE 2500, THEN ON TRACK 016.77 TO CROSS SMGLR AT OR ABOVE 4000, THEN ON TRACK 014.51 TO SONNC, THEN ON TRACK 295.01 TO CROSS AHABB AT OR ABOVE 6000, THEN ON TRACK 295.48 TO LINKE, THEN ON TRACK 294.98 TO CROSS KEEGN AT OR ABOVE 10000, THENCE ...

TAKEOFF RWY 14: CLIMB ON HEADING 141.17, TO INTERCEPT COURSE 088.00 TO CROSS CRRMN AT OR ABOVE 2500, THEN ON TRACK 016.77 TO CROSS SMGLR AT OR ABOVE 4000, THEN ON TRACK 014.51 TO SONNC, THEN ON TRACK 295.01 TO CROSS AHABB AT OR ABOVE 6000, THEN ON TRACK 295.48 TO LINKE, THEN ON TRACK 294.98 TO CROSS KEEGN AT OR ABOVE 10000, THENCE ...

TAKEOFF RWY 28R: CLIMB ON HEADING 278.79 TO 520, THEN DIRECT TO CROSS CRYER AT OR ABOVE 2500, THEN ON TRACK 307.93 TO CROSS UTLEY AT OR ABOVE 4000, THEN ON TRACK 330.36 TO CROSS KEEGN AT OR ABOVE 10000, THENCE ...

...ON TRACK 280.02 TO CROSS OLAKE AT OR ABOVE 12000, THEN ON TRANSITION. EXPECT CLEARANCE TO FILED ALTITUDE WITHIN 10 MINUTES AFTER DEPARTURE.

TAKEOFF RWY 32: CLIMB ON HEADING 321.18 TO 520, THEN DIRECT BAYBE, THEN ON TRACK 313.57 TO CROSS KEEGN AT OR ABOVE 10000, THENCE ...

...ON TRACK 280.02 TO CROSS OLAKE AT OR ABOVE 12000, THEN ON TRANSITION. MAINTAIN ATC ASSIGNED ALTITUDE, EXPECT CLEARANCE TO FILED ALTITUDE WITHIN 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
JAYMC	OLAKE1.JAYMC	OLAKE	JAYMC	TRACK 266.56	31.85	FL180	1400	

PROCEDURAL DATA NOTES:

NOTE: RNAV 1.
NOTE: RADAR REQUIRED.
NOTE: DME/DME/IRU OR GPS REQUIRED.
NOTE: TURBO-JETS ONLY.
NOTE: IF UNABLE TO ACCEPT MINIMUM CLIMB RATES, ADVISE ATC ON INITIAL CONTACT.
NOTE: ATC ASSIGNED ONLY, EXCEPT FOR AIRCRAFT FILED AT OR ABOVE 12000.

TAKEOFF MINIMUMS:

RWY 10L, 14, 28R, 32: STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 520.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:**LOST COMMUNICATIONS PROCEDURES:**

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
OLAKE	ONE	OLAKE1.OLAKE	NONE		<i>12 AUG 2021</i>

ADDITIONAL FLIGHT DATA:

REFERENCE MAGVAR: KPBI 6W EPOCH REAR 2010

DME/DME ASSESSMENT: SAT RNP 2.0

CHART: TOP ALTITUDE: RWY 10L, 14, 28L: 12000

CHART: TOP ALTITUDE: RWY 32: ASSIGNED BY ATC.

CHART: MINIMUM CROSSING ALTITUDE AT KEEGN AT OR ABOVE 10000.

AIRPORTS SERVED:

<u>AIRPORT NAME</u>	<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>
PALM BEACH INTL	KPBI	WEST PALM BEACH	FL

COMMUNICATIONS:

ATIS, CLNC DEL, GND CON, TOWER, PBI DEP CON

FIXES AND/OR NAVAIDS:**REMARKS:**

THE ENVIRONMENTAL REVIEW UNDER ORDER 1050.1 (LATEST EDITION) AND THE NOISE SCREENING HAVE BEEN ACCOMPLISHED.

FLIGHT INSPECTED BY

JEFFREY ECKMAN

*Digitally signed by***JOHN BORDY**

May 27, 2021

OFFICE

FICO

DATE

05/24/2021

DEVELOPED BY

ANA Y. VEGA

*Digitally signed by***ANA Y VEGA**

Apr 19, 2021

OFFICE

AJV-A422

DATE

03/08/2021

APPROVED BY

MARLON ROBINSON

*Digitally signed by***JOHN BORDY**

May 27, 2021

OFFICE

AJV-A420

DATE**TITLE**

MANAGER

REQUIRED EFFECTIVE DATE

ROUTINE

COORDINATED WITH:
A4A ☒
ALPA ☒
AOPA ☒
APA ☒
HAI ☐
NBAA ☒
OTHER: ZMA, PBI APP CON, PBI ATCT, AMGR
CHANGES - REASONS:

ORIGINAL PROCEDURE.

 QUALITY
20
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
OLAKE		ONE		OLAKE1.OLAKE		NONE			<i>12 AUG 2021</i>
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
RW10L (AER)*	264058.97N/0800616.92W*	N	-	-	-	-			*DISPL THLD (1200.0 FT)
520 MSL	-	-	-	VA	092.78	-	AT/ABOVE 520		CG 500 FT/NM TO 520
CRRMN	264039.96N/0795903.47W	Y	FB	DF	-	-	AT/ABOVE 2500		
SMGLR	264354.84N/0795822.18W	Y	FB	TF	010.77	3.30	AT/ABOVE 4000		
SONNC	264724.82N/0795747.15W	Y	FB	TF	008.51	3.53			
AHABB	264832.70N/0800126.85W	Y	FB	TF	289.01	3.47	AT/ABOVE 6000		
LINKE	264948.65N/0800526.30W	Y	FB	TF	289.48	3.79			
KEEGN	265615.25N/0802625.57W	Y	FB	TF	288.98	19.84	AT/ABOVE 10000		
RW14 (AER)	264130.60N/0800614.48W	N	-	-	-	-			
	-	-	-	VI	135.17	2.16			CG 500 FT/NM TO 520
CRRMN	264039.96N/0795903.47W	Y	FB	CF	082.00	4.96	AT/ABOVE 2500		
SMGLR	264354.84N/0795822.18W	Y	FB	TF	010.77	3.30	AT/ABOVE 4000		
SONNC	264724.82N/0795747.15W	Y	FB	TF	008.51	3.53			
AHABB	264832.70N/0800126.85W	Y	FB	TF	289.01	3.47	AT/ABOVE 6000		
LINKE	264948.65N/0800526.30W	Y	FB	TF	289.48	3.79			
KEEGN	265615.25N/0802625.57W	Y	FB	TF	288.98	19.84	AT/ABOVE 10000		
RW28R (AER)*	264055.13N/0800448.94W*	N	-	-	-	-			*DISPL THLD (811.0 FT)
520 MSL	-	-	-	VA	272.79	-	AT/ABOVE 520		CG 500 FT/NM TO 520
CRYER	264112.90N/0801215.10W	Y	FB	DF	-	-	AT/ABOVE 2500		
UTLEY	264322.89N/0801607.46W	Y	FB	TF	301.93	4.09	AT/ABOVE 4000		

QUALITY
20
CHECKED

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
OLAKE		ONE		OLAKE1.OLAKE		NONE			<i>12 AUG 2021</i>
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
KEEGN	265615.25N/0802625.57N	Y	FB	TF	324.36	15.80	AT/ABOVE 10000		
RW32 (AER)*	264044.85N/0800523.87W*	N	-	-	-	-			*DISPL THLD (418.0 FT)
520 MSL	-	-	-	VA	315.18	-	AT/ABOVE 520		CG 500 FT/NM TO 520
BAYBE	264507.52N/0801015.74W	Y	FB	DF	-	-			
KEEGN	265615.25N/0802625.57W	Y	FB	TF	307.57	18.23	AT/ABOVE 10000		
KEEGN	265615.25N/0802625.57W	Y	-	IF	-	-	AT/ABOVE 10000		
OLAKE	265729.75N/0804631.26W	Y	FB	TF	274.02	18.00	AT/ABOVE 12000		
OLAKE	265729.75N/0804631.26W	Y	-	IF	-	-	AT/ABOVE 12000		OLAKE1.JAYMC
JAYMC	265851.00N/0812208.00W	Y	FB	TF	272.56	31.85			

