

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
REEDSBURG, WI	REEDSBURG MUNI	05 APR 2012	2

TAKEOFF MINIMUMS:

RWY 7, 25: NA-OBSTACLES

RWY 18: STANDARD WITH MINIMUM CLIMB OF 505 FT PER NM TO 1400 OR 400-1 3/4 WITH MINIMUM CLIMB OF 215 FT PER NM TO 2000 OR 800-2 1/2 FOR CLIMB IN VISUAL CONDITIONS.

RWY 36: 400-2 OR STANDARD WITH MINIMUM CLIMB OF 300 FT PER NM TO 1400.

TEXTUAL DEPARTURE PROCEDURES:

RWY 18: FOR CLIMB IN VISUAL CONDITIONS: CROSS REEDSBURG MUNI AIRPORT AT OR ABOVE 1600 MSL BEFORE PROCEEDING ON COURSE. WHEN EXECUTING VCOA, NOTIFY ATC PRIOR TO DEPARTURE.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 18: TREES BEGINNING 22 FT FROM DER, 6 FT RIGHT OF CENTERLINE, UP TO 88 FT AGL/1031 FT MSL. TRAIN AND RAILROAD TRACKS 99 FT FROM DER, RIGHT TO LEFT OF CENTERLINE, 23 FT AGL/900 FT MSL. TERRAIN BEGINNING 286 FT FROM DER, 83 FT RIGHT OF CENTERLINE, 1033 FT MSL. VEHICLES ON ROAD 571 FT FROM DER, RIGHT TO LEFT OF CENTERLINE, 15 FT AGL/1033 FT MSL. T-L TOWER 3633 FT FROM DER, RIGHT TO LEFT OF CENTERLINE, UP TO 80 FT AGL/1009 FT MSL. TREES BEGINNING 27 FT FROM DER, 6 FT LEFT OF CENTERLINE, UP TO 89 FT AGL/1032 FT MSL. POLE 3842 FT FROM DER, 39 FT LEFT OF CENTERLINE, UP TO 76 FT AGL/997 FT MSL. TERRAIN BEGINNING 5518 FT FROM DER, 14 FT LEFT OF CENTERLINE, 1033 FT MSL.

NOTE: RWY 36: VERTICAL STRUCTURES BEGINNING 23 FT FROM DER, 62 FT RIGHT AND LEFT OF CENTERLINE, UP TO 21 FT AGL/942 FT MSL. VEHICLE ON ROAD 44 FT FROM DER, LEFT TO RIGHT OF CENTERLINE, 15 FT AGL/962 FT MSL. BUILDINGS BEGINNING 79 FT FROM DER, 5 FT RIGHT OF CENTERLINE, UP TO 29 FT AGL/1050 FT MSL. TREES BEGINNING 100 FT FROM DER, 12 FT RIGHT OF CENTERLINE, UP TO 40 FT AGL/1041 FT MSL. FENCES BEGINNING 121 FT FROM DER, RIGHT AND LEFT OF CENTERLINE, UP TO 24 FT AGL/925 FT MSL. SIGNS BEGINNING 196 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 38 FT AGL/939 FT MSL. PARKING LOT 198 FT FROM DER, 295 FT RIGHT OF CENTERLINE, 13 FT AGL/914 FT MSL. POLES BEGINNING 204 FT FROM DER, RIGHT AND LEFT OF CENTERLINE, UP TO 102 FT AGL/1043 FT MSL. LIGHT SUPPORT STRUCTURES BEGINNING 291 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 44 FT AGL/945 FT MSL. BUILDINGS BEGINNING 328 FT FROM DER, 107 FT LEFT OF CENTERLINE, UP TO 55 FT AGL/976 FT MSL. TERRAIN BEGINNING 397 FT FROM DER, 176 FT RIGHT OF CENTERLINE, UP TO 915 FT MSL. FLAG POLES 825 FT FROM DER, 158 FT LEFT OF CENTERLINE, UP TO 37 FT AGL/978 FT MSL. TREES BEGINNING 1032 FT FROM DER, 28 FT LEFT OF CENTERLINE, UP TO 40 FT AGL/1041 FT MSL.

CONTROLLING OBSTACLES:

RWY18: 1266 FT MSL TREE, 433005.68N/0895837.06W; 1104 FT MSL TREE, 432943.39N/0895843.98W; 1253 FT MSL TREE 433008.77N/0895840.93W; VCOA 1659 FT MSL AAO 432615N/0895836W.

RWY 36: 1263 FT MSL TREE, 433330.06N/0895901.57W; 1160 FT MSL TREE 433334.40N/0895906.50W.

QUALITY
CHECKED

7112-6
Rdb
4/5/12

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
REEDSBURG, WI	REEDSBURG MUNI		2

TAKEOFF MINIMUMS:

RWY 7, 25: NA-OBSTACLES

RWY 18: STANDARD WITH MINIMUM CLIMB OF 505 FT PER NM TO 1400 OR 400-1 3/4 WITH MINIMUM CLIMB OF 215 FT PER NM TO 2000 OR 800-2 1/2 FOR CLIMB IN VISUAL CONDITIONS.

RWY 36: 400-2 OR STANDARD WITH MINIMUM CLIMB OF 300 FT PER NM TO 1400.

TEXTUAL DEPARTURE PROCEDURES:

RWY 18: FOR CLIMB IN VISUAL CONDITIONS: CROSS REEDSBURG MUNI AIRPORT AT OR ABOVE 1600 MSL BEFORE PROCEEDING ON COURSE. WHEN EXECUTING VCOA, NOTIFY ATC PRIOR TO DEPARTURE.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 18: TREES BEGINNING 22 FT FROM DER, 6 FT RIGHT OF CENTERLINE, UP TO 88 FT AGL/1031 FT MSL. TRAIN AND RAILROAD TRACKS 99 FT FROM DER, RIGHT TO LEFT OF CENTERLINE, 23 FT AGL/900 FT MSL. TERRAIN BEGINNING 286 FT FROM DER, 83 FT RIGHT OF CENTERLINE, 1033 FT MSL. VEHICLES ON ROAD 571 FT FROM DER, RIGHT TO LEFT OF CENTERLINE, 15 FT AGL/1033 FT MSL. T-L TOWER 3633 FT FROM DER, RIGHT TO LEFT OF CENTERLINE, UP TO 80 FT AGL/1009 FT MSL. TREES BEGINNING 27 FT FROM DER, 6 FT LEFT OF CENTERLINE, UP TO 89 FT AGL/1032 FT MSL. POLE 3842 FT FROM DER, 39 FT LEFT OF CENTERLINE, UP TO 76 FT AGL/997 FT MSL. TERRAIN BEGINNING 5518 FT FROM DER, 14 FT LEFT OF CENTERLINE, 1033 FT MSL.

NOTE: RWY 36: VERTICAL STRUCTURES BEGINNING 23 FT FROM DER, 62 FT RIGHT AND LEFT OF CENTERLINE, UP TO 21 FT AGL/942 FT MSL. VEHICLE ON ROAD 44 FT FROM DER, LEFT TO RIGHT OF CENTERLINE, 15 FT AGL/962 FT MSL. BUILDINGS BEGINNING 79 FT FROM DER, 5 FT RIGHT OF CENTERLINE, UP TO 29 FT AGL/1050 FT MSL. TREES BEGINNING 100 FT FROM DER, 12 FT RIGHT OF CENTERLINE, UP TO 40 FT AGL/1041 FT MSL. FENCES BEGINNING 121 FT FROM DER, RIGHT AND LEFT OF CENTERLINE, UP TO 24 FT AGL/925 FT MSL. SIGNS BEGINNING 196 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 38 FT AGL/939 FT MSL. PARKING LOT 198 FT FROM DER, 295 FT RIGHT OF CENTERLINE, 13 FT AGL/914 FT MSL. POLES BEGINNING 204 FT FROM DER, RIGHT AND LEFT OF CENTERLINE, UP TO 102 FT AGL/1043 FT MSL. LIGHT SUPPORT STRUCTURES BEGINNING 291 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 44 FT AGL/945 FT MSL. BUILDINGS BEGINNING 328 FT FROM DER, 107 FT LEFT OF CENTERLINE, UP TO 55 FT AGL/976 FT MSL. TERRAIN BEGINNING 397 FT FROM DER, 176 FT RIGHT OF CENTERLINE, UP TO 915 FT MSL. FLAG POLES 825 FT FROM DER, 158 FT LEFT OF CENTERLINE, UP TO 37 FT AGL/978 FT MSL. TREES BEGINNING 1032 FT FROM DER, 28 FT LEFT OF CENTERLINE, UP TO 40 FT AGL/1041 FT MSL.

CONTROLLING OBSTACLES:

RWY18: 1266 FT MSL TREE, 433005.68N/0895837.06W; 1104 FT MSL TREE, 432943.39N/0895843.98W; 1253 FT MSL TREE 433008.77N/0895840.93W; VCOA 1659 FT MSL AAO 432615N/0895836W.

RWY 36: 1263 FT MSL TREE, 433330.06N/0895901.57W; 1160 FT MSL TREE 433334.40N/0895906.50W.



U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
REEDSBURG, WI	REEDSBURG MUNI		2

REMARKS:

RWY 7/25 IFR DEPARTURES NA WITH FPT AND AMGR CONCURRENCE.

FLIGHT INSPECTED BY:

Curt Draper

12/20/11

REQUIRED EFFECTIVE DATE:

ROUTINE

DEVELOPED BY:

BETTY RICHARDS

AJV-353

09/20/2011

APPROVED BY:

LARRY STROUT

AJV-353

DEC 23 2011

COORDINATED WITH:

AOPA, NBAA, ALPA, AMGR, MSN APP CON, ZAU

CHANGES:

1. CHANGED TAKE-OFF MINIMUMS FOR RWYS 7/25 FROM STANDARD TO NA.
2. CHANGED TAKE-OFF MINIMUMS FOR RWY 18 FROM 400—1 TO 400—1 ¾ WITH A MINIMUM CLIMB OF 215 FT PER NM TO 2000 OR STANDARD WITH A MINIMUM CLIMB OF 505 FT PER NM TO 1400 OR 800—2 ½ FOR CLIMB IN VISUAL CONDITIONS. ADDED VCOA.
3. CHANGED TAKE-OFF MINIMUMS FOR RWY 36 FROM 300—1 TO 400—2 OR STANDARD WITH A MINIMUM CLIMB OF 300 FT PER NM TO 1400.
4. ADDED TEXTUAL DEPARTURE PROCEDURE FOR VCOA.
5. ADDED TAKE-OFF OBSTACLE NOTES.
6. UPDATED CONTROLLING OBSTACLES.

REASONS:

1. UNABLE TO VERIFY OBSTACLES THAT PENETRATE RWY 7/25 DEPARTURE SLOPES.
2. NEW CONTROLLING OBSTACLES.
3. NEW CONTROLLING OBSTACLES.
4. ADDED OPTION OF VCOA.
5. IAW 8260.46D, TABLE 1, 2)
6. NEW SURVEY DATA.

QUALITY
CHECKED