

**Federal Aviation
Administration**

Transmittal Letter 19-08

February 22, 2018

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
25-Apr-19	PA	Philadelphia	Philadelphia Intl	8/8435	2/14/19	RNAV (GPS) RWY 26, Amdt 1C

AIRAC Date: 25 APRIL 2019

FDC **8/8435** PHL IAP PHILADELPHIA INTL, Philadelphia, PA. RNAV (GPS) RWY 26, AMDT 1C... LNAV MDA 540/HAT 504 ALL CATS, VISIBILITY CAT C, D RVR 55. CIRCLING CAT A MDA 540/HAA 504, CAT B MDA 600/HAA 564, CAT C MDA 620/HAA 584, CAT D MDA 720/HAA 684. VISIBILITY CAT A, B 1, CAT C 1 1/2, CAT D 2 1/4. CHART CIRCLING ICON. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -12C (11F) OR ABOVE 54C (130F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -12C OR ABOVE 54C. DELETE NOTE: FOR INOP ALS, INCREASE LPV ALL CATS VISIBILITY 3/8 SM, INCREASE LNAV CATS A AND B TO RVR 5000. CHART NOTE: FOR INOP ALS, INCREASE LPV ALL CATS VISIBILITY 3/8 SM, INCREASE LNAV CATS A AND B TO RVR 5500. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. THIS IS RNAV (GPS) RWY 26, AMDT 1D.
1809261133-PERM