

U.S. Department of Transportation Federal Aviation Administration		ILS - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.29		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	ILS: AT THE DH. LOC: 5.59 MILES AFTER JULIP LOM CLIMB TO 1400 THEN CLIMBING RIGHT TURN TO 2600 VIA DNV R-243 TO BUBLE INT AND HOLD; OR WHEN DIRECTED BY ATC, CLIMB TO 1400 THEN CLIMBING RIGHT TURN TO 2600 DIRECT JULIP LOM AND HOLD NE, RT, 209.20 INBOUND. (ADF REQUIRED)	
DNV VORTAC	JULIP LOM	099.50/1.29	2600	ADDITIONAL FLIGHT DATA: HOLD NE, RT, 243.06 INBOUND. CHART FAS OBST: 803 ELEVATOR 4016177N/0873236W DO NOT CHART ALTERNATE MISSED APPROACH HOLDING AT JULIP LOM. CHART TDZE 697.	
BATAM INT (IAF)	COSMA INT (NO PT)	105.48/7.13 (RBS R-105) (DNV LR-021)	2600		
BVT VORTAC (IAF)	COSMA (NO PT)	241.48/19.38	2600		
COSMA	JULIP LOM	209.20/8.02	2600		
1. PT <u>R</u> SIDE OF COURSE <u>029.20</u> OUTBOUND <u>2600</u> FT WITHIN <u>10</u> MILES OF <u>JULIP LOM</u> (IAF) 2. 3. FAC: <u>209.20</u> FAF: <u>JULIP LOM</u> DIST FAF TO MAP: <u>5.59</u> THLD: <u>5.59</u> 4. MIN. ALT: <u>JULIP LOM 2600</u> 5. DIST TO THLD FROM OM: <u>5.59</u> MM: IM: 150 HAT: 100 HAT: GS ANT: <u>894</u> 6. MIN GS INCPT: <u>2600</u> GS ALT AT: OM: <u>2552</u> MM: - IM: - 7. GS ANGLE: <u>3.00</u> TCH: <u>45.9</u> 8. MSA FROM: <u>DN LOM 180-270 3000, 270-180 2400</u>				MAG VAR: 0 EPOCH YEAR: 80	
MINIMUMS					
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	ILS: STANDARD @ LOC: STANDARD @
CATEGORY ==>	A		B		C
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS
S-ILS 21	897	1/2	200	897	1/2
S-LOC 21	1060	1/2	363	1060	1/2
CIRCLING	1120	1	423	1160	1
NOTES: CHART NOTES: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE UNIVERSITY OF ILLINOIS-WILLARD ALTIMETER @ NA WHEN LOCAL WEATHER NOT AVAILABLE. SETTING AND INCREASE ALL DAS/MDAS 100 FEET. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON BVT VORTAC AIRWAY RADIALS 186 CW 271.					
CITY AND STATE		ELEVATION: 697 TDZE: 697		FACILITY IDENTIFIER: I-DNV	
DANVILLE, IL		AIRPORT NAME: VERMILION COUNTY		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: MAR 15 2007	
				ILS OR LOC RWY 21, AMDT 7	
				SUP: ILS RWY 21	
				AMDT: 6	
				DATE 25 MAR 99	

