

**Federal Aviation
Administration**

Transmittal Letter 15-23

September 25, 2015

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DAT	SUBJECT
12-Nov-15	NC	Lincolnton	Lincolnton-Lincoln County Rgnl	5/3184	09/08/15	RNAV (GPS) RWY 5, Amdt 1A

AIRAC Date: 12 November 2015

FDC **5/3184** IPJ IAP LINCOLNTON-LINCOLN COUNTY RGNL, LINCOLNTON, NC. RNAV (GPS) RWY 5, AMDT 1A... CIRCLING CAT A/B MDA 1360/HAA 483, CAT C/D MDA 1640/HAA 762, CAT C VIS 2 1/4, CAT D VIS 2 1/2. CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHARLOTTE ALTIMETER SETTING AND INCREASE ALL DA 63 FEET AND ALL MDA 80 FEET, INCREASE LPV CATS A-C VISIBILITY 1/8 MILE, LNAV-VNAV CATS A-C, LNAV CATS C/D AND CIRCLING CATS C/D VISIBILITY 1/4 MILE. CHART CIRCLING ICON. ALTERNATE MINIMUMS: STANDARD, EXCEPT CAT C 800-2 1/4, CAT D 800-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 5, AMDT 1B. 1509012050-PERM