# FEDERAL AVIATION ADMINISTRATION

# FLIGHT STANDARDS SERVICE ILS STANDARD INSTRUMENT APPROACH PROCEDURE

# TITLE 14 CFR PART 97.29

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.

Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

AIRPORT IDPROCEDURE NAMEORIGINAL/AMENDMENTCITYSTATEKMYRILS OR LOC RWY 365MYRTLE BEACHSC

 AIRPORT ELEVATION
 TDZE
 SUPERSEDED
 ORIGINAL/AMENDMENT
 DATED
 MAG VAR
 EPOCH YEAR

 25
 25
 ILS OR LOC RWY 36
 4
 02/04/2016
 9W
 2020

FACILITY
I-BSQ

COORDINATES OF FACILITIES
ACTUAL EFFECTIVE DATE
REQUIRED EFFECTIVE DATE
ROUTINE

CANCEL/SUSPEND
ROUTINE

TERMINAL ROUTES

| FROM        | FIX TYPE | <u>TO</u>   | FIX TYPE | LEG TYPE | FO/FB | RNP | <u>COURSE</u> | DISTANCE | <u>ALTITUDE</u> |
|-------------|----------|-------------|----------|----------|-------|-----|---------------|----------|-----------------|
| CHACA/RADAR | IF       | PORKE/RADAR |          |          |       |     | 357.21        | 6.01     | 1600            |

**Electronic Version** 

#### MISSED APPROACH

MAP:

ILS: DA LOC: 4.79 NM AFTER PORKE/RADAR

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 3000 ON HEADING 357.21 EXPECT RADAR VECTORS TO KOOKE INT/FAY 62.86 DME AND HOLD.

#### ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)

2. PROFILE STARTS AT CHACA

**3. FAC:** 357.21 FAF: PORKE/RADAR DIST FAF TO MAP: 4.79 DIST FAF TO THLD: 4.79

4. MIN ALT: CHACA/RADAR 1600, PORKE/RADAR 1600, SOMVE/RADAR 580

5. DIST TO THLD FROM OM: MM: IM: 150 HAT: GS ANT: 1063

**6. MIN GS INCPT**: 1600 **GS ALT AT PFAF**: PORKE/RADAR 1600 **OM**: **MM**: **IM**:

**7. GP ANGLE**: 3.00 **34:1**: **20:1**: TCH: 52.1

8. MSA FROM: CRE VORTAC 2100

**EQUIPMENT REQUIREMENTS NOTES:** 

RADAR REQUIRED

NOTES:

CHART NOTE: FOR INOPERATIVE ALS INCREASE S-LOC 36 CATS D/E VISIBILITY TO RVR 5000. CHART PROFILE NOTE: VGSI AND ILS GLIDEPATH NOT COINCIDENT. (VGSI ANGLE {ANGLE}/TCH{FEET})

Page 1 of 2

AIRPORT IDPROCEDURE NAMEORIGINAL/AMENDMENTCITYSTATEKMYRILS OR LOC RWY 365MYRTLE BEACHSC

# **ADDITIONAL FLIGHT DATA:**

CHART CIRCLING ICON.
CHART 200 MSL SHIP 333541N/0785351W.
HOLD N, RT, 190.00 INBOUND.
CHART FAS OBST: 110 TREE (45-067230) 333927N/0785534W.
CHART W177A.

**MINIMUMS:** 

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ILS: STANDARD - NA WHEN CONTROL TOWER CLOSED.; LOC: STANDARD - CAT D 800-2 1/4, CAT E 800-2 1/2, NA WHEN CONTROL TOWER CLOSED.

| CATEGORY:  | Α      |            | В       |        | С          |         |        | D          |         |        | E          |         |        |            |         |
|------------|--------|------------|---------|--------|------------|---------|--------|------------|---------|--------|------------|---------|--------|------------|---------|
| FINAL TYPE | DA/MDA | <u>VIS</u> | HAT/HAA |
| S-ILS 36   | 225    | 4000       | 200     | 225    | 4000       | 200     | 225    | 4000       | 200     | 225    | 4000       | 200     | 225    | 4000       | 200     |
| S-LOC 36   | 360    | 4000       | 335     | 360    | 4000       | 335     | 360    | 4000       | 335     | 360    | 4000       | 335     | 360    | 4000       | 335     |
| CIRCLING   | 560    | 1          | 535     | 560    | 1          | 535     | 700    | 2          | 675     | 700    | 2 1/4      | 675     | 700    | 2 1/2      | 675     |

# **CHANGES - REASONS**

- 1. REMOVED "\*LOC ONLY" FROM NOTES NO LONGER REQUIRED PER 8260.19I CHAPTER 8.
- 2. CHANGED MISSED APPROACH HOLDING FIX FROM HYW NDB TO KOOKE HYW NDB WILL BE DECOMMISSIONED.
- 3. REMOVED ALTERNATE MISSED APPROACH CRE VORTAC DME IS OUT OF SERVICE INDEFINITELY.
- 4. ADDITIONAL FLIGHT DATA NOTE CHANGED FROM CHART FAS OBST: 106 TREE 333924N/0785530W TO CHART FAS OBST: 110 TREE (45-067230) 333927N/0785534W NEW CONTROLLING OBSTACLE.
- 5. CIRCLING CATS C, D, E MDA/HAA CHANGED FROM 740/715 TO 700/675 ACCURACY CODE ADJUSTMENT.
- 6. RADAR REQUIRED NOTE ENTERED UNDER EQUIPMENT REQUIREMENT NOTES AND CHART NOTE: ADF AND RADAR REQUIRED DELETED- FAA ORDER 8260-191 8-6-8.A.
- 7. CHANGED CHART NOTE FROM CHART NOTE: FOR INOPERATIVE MALSF INCREASE S-LOC 36 CATS D/E VISIBILITY TO RVR 5000 TO CHART NOTE: FOR INOPERATIVE ALS INCREASE S-LOC 36 CATS D/E VISIBILITY TO RVR 5000 FAA ORDER 8260-19I 8-6-11.O(3)D
- 8. ALTERNATE MINUMUMS: ADDED NA WHEN CONTROL TOWER CLOSED TO ILS AND LOC LOCALZER FACILITY NOT MONITORED WHEN THE TOWER IS CLOSED.

#### COORDINATED WITH:

APA 🔯 A4A X ALPA X AOPA X HAI 🗌 NBAA X OTHER: ZJX, MYR APP CON, AIRPORT MANAGER, MYR ATCT Digitally signed by **FLIGHT CHECKED BY OFFICE** DATE DAVID TEFFETELLER ERIC L GEYER **FPO** 08/25/2022 Sep 01, 2022 **DEVELOPED BY OFFICE** DATE Digitally signed by FRANK MOORE **AJV-A433** 03/08/2022 FRANK MOORE Digitally signed by **APPROVED BY OFFICE** DATE TITLE May 26, 2022 DAVID TEFFETELLER MANAGER LONNIE EVERHART AJV-A430 Sep 01, 2022