

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: VOYNU/2.14 DME FIX									
APLES/12.23 DME CCW (IAF)		BYTHE/12.23 DME		12.23 DME ARC				6600		CLIMB TO 3500 THEN CLIMBING RIGHT TURN TO 6000 VIA HEADING 300 AND VCV R-269 TO ETHER INT AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, LT, 268.88 INBOUND. CHART BUCKHORN MOA. CHART R-2515. CHART VCV R-011 AT BYTHE. CHART VCV R-089 AT APLES. UNCAL TO RW17: 3.00/75. FAC CROSSES RWY C/L EXTENDED 2985 FROM THLD.									
BYTHE/12.23 DME CCW		WENOD/12.23 DME		12.23 DME ARC (VCV LR-360)				5200											
WENOD/12.23 DME (IF)		UNCAL/6.08 DME		170.14 / 6.15 (VCV R-350)				4300											
1. PT <u>NA</u> SIDE OF COURSE <u>OUTBOUND</u> <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. PROFILE STARTS AT WENOD/12.23 DME 3. FAC <u>170.14</u> FAF <u>UNCAL/6.08 DME</u> DIST FAF TO MAP <u>—</u> THLD <u>4.43</u> 4. MIN. ALT <u>WENOD 5200, UNCAL 4300</u> 8. MSA FROM: <u>VCV VOR/DME 090-180 10000, 180-270 11300, 270-090 7600</u>														MAG VAR: 14E		EPOCH YEAR: 1995			
MINIMUMS																			
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: NA		STANDARD @					
CATEGORY =====>		A		B		C		D		E									
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA			
S-17		3200	5000	375	3200	5000	375	3200	5000	375	3200	6000	375						
CIRCLING		3360	1	475	3420	1	535	3420	1 1/2	535	3580	2 1/4	695						
NOTES: CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED USE EDWARDS AFB ALTIMETER SETTING AND INCREASE ALL MDA 160 FEET. INCREASE ALL VISIBILITIES 1/2 MILE. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT APLES VIA V394 AND V442 SOUTHWEST BOUND.																			
CITY AND STATE VICTORVILLE, CA				ELEVATION: 2885 TDZE: 2825				FACILITY IDENTIFIER: VCV				PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME RWY 17, AMDT 1 15 JAN 2009				SUP			
				AIRPORT NAME:												AMDT ORIG-B			
				SOUTHERN CALIFORNIA LOGISTICS												DATE 01/18/2007			

 QUALITY
2
CHECKED

**VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - FAR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE

VICTORVILLE, CA

ELEVATION: 2885 TDZE: 2825

AIRPORT NAME:

SOUTHERN CALIFORNIA LOGISTICS

FACILITY
IDENTIFIER:
VCV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR/DME RWY 17, AMDT 1

15 JAN 2009

SUP:

AMDT: ORIG-B

DATED: 01/18/2007