

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
ILS STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.29

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> KXNA	<u>PROCEDURE NAME</u> ILS OR LOC RWY 34R	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>CITY</u> FAYETTEVILLE/SPRINGDALE/RO GERS	<u>STATE</u> AR		
<u>AIRPORT ELEVATION</u> 1288	<u>TDZE</u> 1273	<u>SUPERSEDED</u>	<u>ORIGINAL/AMENDMENT</u> NONE	<u>DATED</u>	<u>MAG VAR</u> 1E	<u>EPOCH YEAR</u> 2020
<u>FACILITY</u> I-FBS	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 20 APRIL 2023	<u>REQUIRED EFFECTIVE DATE</u> 04/20/2023	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE
WARAR INT/I-FBS 19.27 DME	IAF	LNSDY INT/I-FBS 12.87 DME/RADAR	NOPT				338.74	6.40 (I-FBS)	3400
LNSDY INT/I-FBS 12.87 DME/RADAR	IF/IAF	ROGEY/I-FBS 6.89 DME/RADAR					338.74	5.98 (I-FBS)	3000

MISSED APPROACH

MAP:

ILS: DA
LOC: 5.27 NM AFTER ROGEY/I-FBS 6.89 DME/RADAR OR AT I-FBS 1.62 DME

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 1800 THEN CLIMBING RIGHT TURN TO 3400 ON HEADING 163 AND ON RZC VORTAC R-204 TO LNSDY INT/I-FBS 12.87 DME/RADAR AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD S LNSDY, LT, 338.74 INBOUND, 3400 FT. IN LIEU OF PT (IAF), MAX 5700.
3. FAC: 338.74 FAF: ROGEY/I-FBS 6.89
DME/RADAR DIST FAF TO MAP: 5.27 DIST FAF TO THLD: 5.27
4. MIN ALT: LNSDY INT/I-FBS 12.87 DME/RADAR 3400, ROGEY/I-FBS 6.89 DME/RADAR 3000, ZAKAN/I-FBS 3.12 DME/RADAR 1800
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: GS ANT: 1034
6. MIN GS INCPT: 3000 GS ALT AT PFAF: ROGEY/I-FBS 6.89 DME/RADAR 3000 OM: MM: IM:
7. GS ANGLE: 3.00 34:1: 20:1: TCH: 57.8
8. MSA FROM: RZC VORTAC 090-180 4500, 180-270 3600, 270-090 3200

QUALITY
8
CHECKED

