

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION							ILS - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.29							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.						
TERMINAL ROUTES														MISSED APPROACH						
FROM				TO				COURSE AND DISTANCE				ALTITUDE		ILS: DA LOC: 4.72 MILES AFTER VERON LOM/I-TUP 6.06 DME OR AT I-TUP 1.32 DME FIX. CLIMB TO 3000 DIRECT ZUMHA AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 181.89 INBOUND. CHART VDP AT 2.21 DME* *LOC ONLY. DISTANCE VDP TO THLD 0.88 MILES. CHART 494 MSL TOWER 341554N/0884628W. CHART CIRCLING ICON.						
GAGYE/I-TUP 15.36 DME (IF/IAF)				VERON LOM/I-TUP 6.06 DME				001.89 / 9.32 (I-TUP)				2000								
1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)														MAG VAR: 2W EPOCH YEAR: 2015						
2. HOLD S GAGYE, LT, 001.89 INBOUND, 3000 FT. IN LIEU OF PT (IAF)																				
3. FAC: 001.89 FAF: VERON LOM/I-TUP 6.06 DME DIST FAF TO MAP: 4.72 THLD: 4.72																				
4. MIN. ALT: GAGYE 3000, VERON LOM 2000																				
5. DIST TO THLD FROM OM: 4.72 MM: - IM: - 150 HAT: - 100 HAT: - GS ANT: 1050																				
6. MIN GS INCPT: 2000 GS ALT AT: - OM: 1924 MM: - IM: -																				
7. GS ANGLE: 3.00 TCH: 54.7																				
8. MSA FROM:																				
MINIMUMS																				
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A			ILS: STANDARD #			LOC: NA							
CATEGORY >>>>>		A			B			C			D			E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA					
S-ILS 36	546	1/2	200	546	1/2	200	546	1/2	200	546	1/2	200								
S-LOC 36	700	1/2	354	700	1/2	354	700	5/8	354	700	5/8	354								
CIRCLING	800	1	454	800	1	454	900	1 1/2	554	1140	2 1/2	794								
NOTES: CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE COLUMBUS AFB ALTIMETER SETTING AND INCREASE ALL DA 112 FEET, INCREASE ALL MDA 120 FEET AND INCREASE S-LOC 36 CATS C AND D VISIBILITY 3/8 MILE. INCREASE CIRCLING CATS C AND D VISIBILITY 1/2 MILE. FOR INOPERATIVE MALSR WHEN USING COLUMBUS AFB ALTIMETER SETTING, INCREASE S-ILS 36 ALL CATS VISIBILITY 1/2 MILE.																				
# NA WHEN LOCAL WEATHER NOT AVAILABLE. # CAT D 800-2 1/2																				
(SEE FORM 8260-10)																				
CITY AND STATE TUPELO, MS				ELEVATION: 346 TDZE: 346 AIRPORT NAME: TUPELO RGNL				FACILITY IDENTIFIER: I-TUP		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS Y OR LOC Y RWY 36, ORIG 5 MARCH 2015				SUP: AMDT: NONE DATED						



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: GPS AND ADF OR DME REQUIRED.

CHART NOTE: VDP NA WHEN USING COLUMBUS AFB ALTIMETER SETTING.

CHART NOTE: CHART 4 NM ON OUTBOUND LEG OF HOLDING PATTERN AT GAGYE.

CHART PROFILE NOTE: USE I-TUP DME WHEN ON THE LOCALIZER COURSE.

CHART PLANVIEW NOTE: GPS REQUIRED FOR TERMINAL ARRIVAL AREA.

TAA	FROM	TO	ALT
1.	272/30 CW 092/30 (NOPT)	272/15 CW 092/15	4000
2.	272/15 CW 092/15	GAGYE (IF/IAF) (FB)	3000
3.	092/30 CW 272/30	GAGYE (IF/IAF) (FO)	3000

QUALITY
9
CHECKED

CITY AND STATE TUPELO, MS	ELEVATION: 346 TDZE: 346 AIRPORT NAME: TUPELO RGNL	FACILITY IDENTIFIER: I-TUP	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: ILS Y OR LOC Y RWY 36, ORIG 5 MARCH 2015	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION ILS STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.29								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
ARINC SUMMARY - 424-18 - ILS												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	GAGYE	GAGYE	010	IAF	HF	L	FO		001.9 ()	004.0	AA 03000	
		GAGYE	010	FACF	IF		FB				AA 03000	GI 02000
		VERON	020	FAF	CF		FB		002.0 ()	009.3	GI 02000	GS 01924
		RW36	030	MAP	CF		FO		002.0 ()	004.7	AT 00400	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		ZUMHA	040		DF		FO				AA 03000	
		ZUMHA	050		HM	R	FO		181.9 ()	004.0	AA 03000	
POINT DATA		WAYPOINT	LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS			
		ITUP (DME)	N341652.45		W0884615.45		N3416.874		W08846.258			
		GAGYE	N340129.42		W0884609.60		N3401.490		W08846.160			
		VERON	N341049.35		W0884610.87		N3410.823		W08846.181			
		ZUMHA	N342915.05		W0884613.44		N3429.251		W08846.224			
		RW36	N341533.03		W0884611.53		N3415.551		W08846.192			
		ITUP (LOC)	N341653.73		W0884611.73		N3416.896		W08846.196			
RUNWAY DATA			THRESHOLD									
		RWY	ELEVATION		TCH							
		RW36	00346		55							



CITY AND STATE TUPELO, MS	ELEVATION: 346 TDZE: 346 AIRPORT NAME: TUPELO RGNL	FACILITY IDENTIFIER: I-TUP	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: ILS Y OR LOC Y RWY 36, ORIG 5 MARCH 2015	SUP: AMDT: NONE DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
LOC STANDARD INSTRUMENT APPROACH PROCEDURE												
FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.25												
ARINC SUMMARY - 424-18 - LOC												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	GAGYE	GAGYE	010	IAF	HF	L	FO		001.9 ()	004.0	AA 03000	
		GAGYE	010	FACF	IF		FB				AA 03000	
		VERON	020	FAF	CF		FB		002.0 ()	009.3	AA 02000	
		RW36	030	MAP	CF		FO		002.0 ()	004.7	AT 00400	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		ZUMHA	040		DF		FO				AA 03000	
		ZUMHA	050		HM	R	FO		181.9 ()	004.0	AA 03000	
POINT DATA		WAYPOINT	LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS			
		ITUP (DME)	N341652.45		W0884615.45		N3416.874		W08846.258			
		GAGYE	N340129.42		W0884609.60		N3401.490		W08846.160			
		VERON	N341049.35		W0884610.87		N3410.823		W08846.181			
		ZUMHA	N342915.05		W0884613.44		N3429.251		W08846.224			
		RW36	N341533.03		W0884611.53		N3415.551		W08846.192			
		ITUP (LOC)	N341653.73		W0884611.73		N3416.896		W08846.196			
RUNWAY DATA			THRESHOLD									
		RWY	ELEVATION		TCH							
		RW36	00346		55							



CITY AND STATE TUPELO, MS	ELEVATION: 346	TDZE: 346	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: TUPELO RGNL		I-TUP	ILS Y OR LOC Y RWY 36, ORIG	AMDT: NONE
				5 MARCH 2015	DATED: