

**Federal Aviation
Administration**

Transmittal Letter 24-12

April 12, 2024

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
5/16/2024	NJ	Toms River	Ocean County	4/4134	3/29/2024	RNAV (GPS) RWY 6, Orig-C

AIRAC Date: 16 MAY 2024

FDC 4/4134 MJX IAP OCEAN COUNTY, TOMS RIVER, NJ. RNAV (GPS) RWY 6, ORIG-C... CIRCLING CAT A MDA/HAA 540/454, CAT B HAA 474, CAT C HAA 494, CAT D HAA 614. APT ELEV: 86. DELETE PROFILE NOTE: *LNAV ONLY. DELETE ASTERISK FROM MINIMUM ALTITUDE AT XOQUR/1.9 NM TO RW06 720. DELETE ASTRISK FROM VDP AT 1.23 NM TO RW06. CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. DELETE NOTE: DME/DME RNP 0.3 NA. PBN EQUIPMENT REQUIREMENTS NOTE: RNP APCH - GPS. CHANGE NOTE TO READ: RWY 6 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHANGE NOTE TO READ: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS AND LNAV CATS A/B VISIBILITY TO 1. CHANGE NOTE TO READ: FOR INOPERATIVE ALS WHEN USING MC GUIRE FLD (JOINT BASE MC GUIRE DIX LAKEHURST) ALTIMETER SETTING, INCREASE LPV ALL CATS VISIBILITY TO 7/8, LNAV/VNAV ALL CATS VISIBILITY TO 1 1/8, LNAV CATS A/B VISIBILITY TO 1, AND LNAV CATS C/D VISIBILITY TO 1 3/8. THIS IS RNAV (GPS) RWY 6, ORIG-D. 2403291455-PERM