

**Federal Aviation
Administration**

Transmittal Letter 21-15

MAY 28, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/15/2021	LA	Alexandria	Esler Rgnl	1/3996	4/15/2021	RNAV (GPS) RWY 9, Amdt 2A

Airac Date: 15 JULY 2021

FDC 1/3996 ESF IAP ESLER RGNL, ALEXANDRIA, LA. RNAV (GPS) RWY 9, AMDT 2A...
LNAV/VNAV VISIBILITY 1 3/8 ALL CAT. CIRCLING CAT C MDA 740/HAA 628, CAT D MDA
760/648, CAT C VIS 1 3/4. DELETE NOTE: WHEN VGSI INOP, CIRCLING RWY 14/32 NA AT
NIGHT. CHART NOTE: CIRCLING RWY 14, 32 NA AT NIGHT. DELETE NOTE: DME/DME
RNP-0.3 NA. CHART PBN REQUIREMENTS NOTE: RNP APCH-GPS. CHANGE FOR
UNCOMPENSATED BARO-VNAV SYSTEMS NOTE TO READ: FOR UNCOMPENSATED
BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -6C OR ABOVE 54C. CHANGE ALTIMETER
SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE
ALEXANDRIA INTL ALTIMETER SETTING: INCREASE LPV DA TO 331 FEET; INCREASE
LNAV/VNAV DA TO 644 FEET AND ALL VISIBILITY 1/4 SM; INCREASE ALL MDAS 40 FEET
AND CIRCLING VISIBILITY CAT D 1/4. THIS IS RNAV (GPS) RWY 9, AMDT 2B. 2103111312-
PERM