

**Federal Aviation
Administration**

Transmittal Letter 26-20

July 31, 2026

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
9/3/2026	TX	Castroville	Castroville Muni	6/8783	3/17/2026	RNAV (GPS) RWY 34, Amdt 1

AIRAC Date: 3 September 2026

FDC 6/8783 CVB IAP CASTROVILLE MUNI, CASTROVILLE, TX. RNAV (GPS) RWY 34, AMDT 1... LNAV CAT C VISIBILITY 1 1/4. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE MIN ALT AT TAAHD TO READ: TAAHD/1.60 NM TO RW34 1300. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SKF ALTIMETER SETTING: INCREASE LPV DA TO 1064 FEET; INCREASE LNAV/VNAV DA TO 1172 FEET; INCREASE ALL MDAS 60 FEET AND LNAV VISIBILITY CAT C 1/8 SM AND CIRCLING VISIBILITY CAT C 1/4 SM. CHANGE HELICOPTER VISIBILITY REDUCTION NOTE TO READ: RWY 34 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHANGE NIGHT LANDING NOTE TO READ: CIRCLING RWY 16 NA AT NIGHT. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. THIS IS RNAV (GPS) RWY 34, AMDT 1A. 2603161416-PERM