

US DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
EXULE (IF/IAF)	MIVOE (FB)	158.40 / 6.51	1800	LNAV: RW15
				CLIMBING LEFT TURN TO 2500 DIRECT FEBEL AND HOLD.
				ADDITIONAL FLIGHT DATA: HOLD NE, RT, 203.57 INBOUND. CHART FAS OBST: 309 TREE 354949N/0780103W CHART 421 TOWER 355049N/0780024W. MIVOE TO RW15: 3.04/40.

- PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
- HOLD N EXULE, RT, 158.40 INBOUND, 2500 FT. IN LIEU OF PT (IAF)
- FAC: 158.44 FAF: MIVOE DIST FAF TO MAP: 4.95 THLD: 4.95
- MIN. ALT: EXULE 2500, MIVOE 1800
- DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
- MIN GS INCP:        GS ALT AT:        OM:        MM:        IM:
- GS ANGLE:        TCH: 34:1 IS NOT CLEAR
- MSA FROM: RW15 3400

MAG VAR: 8W EPOCH YEAR: 1985

**MINIMUMS**

TAKEOFF:	<input type="checkbox"/> STANDARD	<input checked="" type="checkbox"/> X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	<input type="checkbox"/> X										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	560	1	399	560	1	399	560	1	399	560	1 1/4	399			
CIRCLING	580	1	419	620	1	459	620	1 1/2	459	720	2	559			

**ROCKY MOUNT ALTIMETER SETTING MINIMUMS**

LNAV MDA	580	1	419	580	1	419	580	1 1/4	419	580	1 1/4	419			
CIRCLING	600	1	439	620	1	459	620	1 1/2	459	720	2	559			

NOTES:  
CHART NOTE: DME/DME RNP-0.3 NA.  
CHART NOTE: PROCEDURE NA AT NIGHT.  
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.  
CHART PLANVIEW NOTE: NOPT FOR ARRIVAL AT EXULE ON V194-310 EAST BOUND.  
SEE 8260-10

CITY AND STATE <b>WILSON, NC</b>	ELEVATION: 161 TDZE: 161 AIRPORT NAME: <b>WILSON INDUSTRIAL AIR CENTER</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 15, AMDT 1 APR 10 2008</b>	SUP: AMDT: <b>ORIG</b> DATED <b>03/20/2003</b>
-------------------------------------	--	-------------------------------------	--	--

*TR 08-06*

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**NOTES CONT.**

**CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED USE ROCKY MOUNT ALTIMETER SETTING.**

CITY AND STATE

WILSON, NC

ELEVATION: 161 TDZE: 161

AIRPORT NAME:

WILSON INDUSTRIAL AIR CENTER

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 15, AMDT 1

APR 10 2008

SUP:

AMDT: ORIG

DATED: 03/20/2003

