

**Federal Aviation
Administration**

Transmittal Letter 20-03

December 13, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
1/30/2020	LA	Lake Charles	Chennault Intl	9/8269	11/20/2019	RNAV (GPS) RWY 33, Amdt 1

AIRAC Date: 30 JANUARY 2020

FDC 9/8269 CWF IAP CHENNAULT INTL, LAKE CHARLES, LA. RNAV (GPS) RWY 33, AMDT 1... CIRCLING MDA CAT D 740/HAA 723; VISIBILITY 2 1/4 SM. LNAV VISIBILITY CAT C 1 5/8 SM. ALTERNATE MINIMUMS: STANDARD - CAT D 800-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. CHART CIRCLING ICON. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 49C (120F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 49C. DELETE NOTE: DME/DME RNP-0.3 NA. PBN EQUIPMENT REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: VDP NA WITH LAKE CHARLES RGNL ALTIMETER SETTING. CHART NOTE: VDP NA WHEN USING LAKE CHARLES RGNL ALTIMETER SETTING. DELETE NOTE: WHEN LOCAL ALTIMETER NOT RECEIVED, USE LAKE CHARLES RGNL ALTIMETER SETTING AND INCREASE ALL DA 16 FEET AND ALL MDA 20 FEET. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LAKE CHARLES RGNL ALTIMETER SETTING; INCREASE LPV DA TO 232 FEET; INCREASE LNAV/VNAV DA TO 510 FEET; INCREASE ALL MDA 20 FEET AND LNAV VISIBILITY CAT C 1/8 SM AND CIRCLING CAT D 1/4 SM. THIS IS RNAV (GPS) RWY 33, AMDT 1A. 1911051903-PERM