U.S. Department of Transportation

Federal Aviation Administration

Transmittal Letter 20-04

December 27, 2019

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
1/30/2020	ОН	Urbana	Grimes Field	9/7303	12/16/2019	RNAV (GPS) RWY 2, Amdt 1B

AIRAC Date: 30 JANUARY 2020

FDC 9/7303 I74 IAP GRIMES FIELD, URBANA, OH. RNAV (GPS) RWY 2, AMDT 1B... CIRCLING CAT B MDA 1780/HAA 712, CIRCLING CAT C MDA 1800/HAA 732, CIRCLING CAT C VISIBILITY 2 SM. CHART CIRCLING ICON. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SPRINGFIELD ALTIMETER SETTING AND INCREASE ALL DAS 44 FEET, ALL MDAS 60 FEET, INCREASE LNAV/VNAV ALL CATS VISIBILITY 1/4 SM, AND INCREASE CIRCLING CAT C VISIBILITY 1/4 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SPRINGFIELD ALTIMETER SETTING AND INCREASE ALL DA 44 FEET, ALL MDA 60 FEET, INCREASE LNAV/VNAV ALL CATS VISIBILITY 1/4 SM. THIS IS RNAV (GPS) RWY 2, AMDT 1C. 1912161426-PERM