FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL Altitudes are minimum altitudes unless otherwise indicated Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statue miles or feet RVR unless otherwise indicated.

DP NAME WATTR					<u>NUMBER</u> EIGHT	DP COMPUTER COD WATTR8.WATTR	E <u>SUPERSEDE</u> SEVE		DAT 7/19/2		ACTUAL EFFECTIVE DATE 25 JANUARY 2024
TYPE: OBSTAC	<u>E COPTER</u>	<u>SID</u>		RNAV							
DP ROUTE DESCRIPTION: DP ROUTE DESCRIPTION: TAKEOFF RWY 9: CLIMBING LEFT TURN THENCE TAKEOFF RWY 27, 31: CLIMBING RIGHT TURN THENCE ON 075 BEARING FROM CL LOM TO WATTR INT. MAINTAIN 5400. TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):											
TRANSITION NAME	TRANSIT COMPUTER		<u>FROM</u> FIX/NAVAID			<u>TO</u> NAVAID	COURSE	DISTANCE	MEA	MOCA	CROSSING ALTITUDE/FIXES

PBN REQUIREMENT NOTES:

EQUIPMENT REQUIREMENT NOTES:

ADF REQUIRED

PROCEDURAL DATA NOTES:

TAKEOFF MINIMUMS:

RWY 13: NA - OBSTACLES. RWY 27, 31: STANDARD. RWY 9: 300-1.

TAKEOFF OBSTACLES NOTES:

NOTE: RWY 9: SIGN 46 FT FROM DER, 198 FT RIGHT OF CENTERLINE, 4 FT AGL/295 FT MSL. TERRAIN 54 FT FROM DER, 449 FT RIGHT OF CENTERLINE, 296 FT MSL. SIGN 79 FT FROM DER, 352 FT RIGHT OF CENTERLINE, 4 FT AGL/299 FT MSL. BUILDING, TERRAIN, NAVAID BEGINNING 99 FT FROM DER, 1 FT RIGHT OF CENTERLINE, UP TO 17 FT AGL/314 FT MSL. FENCE 102 FT FROM DER, 526 FT LEFT OF CENTERLINE, 7 FT AGL/300 FT MSL. BUILDING 298 FT FROM DER, 258 FT LEFT OF CENTERLINE, UP TO 377 FT MSL. POLE, VEHICLE ON TRAVERSE WAY BEGINNING 677 FT FROM DER, 630 FT RIGHT OF CENTERLINE, UP TO 32 FT AGL/338 FT MSL. TRANSMISSION LINE 922 FT FROM DER, 630 FT RIGHT OF CENTERLINE, 51 FT AGL/355 FT MSL. TREES BEGINNING 1312 FT FROM DER, 630 FT RIGHT OF CENTERLINE, UP TO 32 FT AGL/338 FT MSL. TREES BEGINNING 1107 FT FROM DER, 391 FT RIGHT OF CENTERLINE, UP TO 420 FT MSL. TREES BEGINNING 1312 FT FROM DER, 630 FT RIGHT OF CENTERLINE, 391 FT RIGHT OF CENTERLINE, UP TO 420 FT MSL. TREES BEGINNING 1312 FT FROM DER, 630 FT RIGHT OF CENTERLINE, 391 FT RIGHT OF CENTERLINE, UP TO 464 FT MSL. TREES BEGINNING 1312 FT FROM DER, 391 FT RIGHT OF CENTERLINE, UP TO 420 FT MSL. TREES BEGINNING 1312 FT FROM DER, 630 FT RIGHT OF CENTERLINE, 391 FT RIGHT OF CENTERLINE, UP TO 420 FT MSL. TREES BEGINNING 1312 FT FROM DER, 630 FT RIGHT OF CENTERLINE, 391 FT RIGHT OF CENTERLINE, UP TO 420 FT MSL. TREES BEGINNING 1312 FT FROM DER, 630 FT RIGHT OF CENTERLINE, 391 FT RIGHT OF CENTERLINE, UP TO 420 FT MSL. TREES BEGINNING 1312 FT FROM DER, 630 FT RIGHT OF CENTERLINE, 391 FT RIGHT OF CENTERLINE, UP TO 420 FT MSL. TREES BEGINNING 1312 FT FROM DER, 630 FT MSL. TREES BEGINNING 1523 FT MSL. TREES BEGINNING 1312 FT FROM DER, 630 FT MSL. TREES BEGINNING 1523 FT MSL. TREES BEGINNING 1512 FT FROM DER, 630 FT MSL. TREES BEGINNING 1523 FT MSL. TREES BEGINNING 1523 FT FROM DER, 197 FT MSL. TREES BEGINNING 1523 FT FROM DER, 192 FT FROM DER, 630 FT MSL. TREES BEGINNING 1523 FT FROM DER, 192 FT FROM DER, 630 FT MSL. TREES BEGINNING 1523 FT FROM DER, 570 FT MSL. TREES BEGINNING 1523 FT FROM DER, 192

NOTE: RWY 27: LIGHTING 10 FT FROM DER, 54 FT RIGHT OF CENTERLINE, 3 FT AGL/287 FT MSL. LIGHTING 10 FT FROM DER, 55 FT LEFT OF CENTERLINE, 3 FT AGL/286 FT MSL. TREES BEGINNING 2709 FT FROM DER, 130 FT LEFT OF CENTERLINE, UP TO 406 FT MSL. TREES BEGINNING 3951 FT FROM DER, 530 FT RIGHT OF CENTERLINE, UP TO 393 FT MSL. TREES BEGINNING 4446 FT FROM DER, 1173 FT LEFT OF CENTERLINE, UP TO 421 FT MSL.



DP NAME WATTR	NUMBER EIGHT	DP COMPUTER CODE WATTR8.WATTR	<u>Superseded Numbe</u> Seven	R DATED 7/19/2018	ACTUAL EFFECTIVE DATE 25 JANUARY 2024
NOTE: RWY 31: TREE, POLE BEGINNING 1 FT FROM DER, 222 FT RIGHT OF TREE 338 FT FROM DER, 524 FT RIGHT OF CENTERLINE, 316 FT MSL. TRE DER, 39 FT LEFT OF CENTERLINE, UP TO 324 FT MSL. TREES BEGINNING	ES BEGINNING 4	431 FT FROM DER, 121 FT RIG	GHT OF CENTERLINE, UP		
CONTROLLING OBSTACLES: RWY 9: 464 FT MSL TREE 480648.75N/1232855.30W (CLIMB GRADIENT, CLI (VISIBILITY).	MB-TO ALTITUD	E), 502 FT MSL TREE 480634.	31N/1232812.98W (CEILIN	G), 465 FT MSL TREE 48	0632.03N/1232805.86W
OBSTACLES MANDATING ODP ROUTE DEVELOPMENT: RWY 9, 27, 31 6654	FT MSL AAO 47	5943.95.40N/1232748.13W.			
<u>MSA</u> : MSA FROM KCLM, 9000					
LOST COMMUNICATIONS PROCEDURES:					
ADDITIONAL FLIGHT DATA: AIRPORT MV: CLM 16E/2020					
AIRPORTS SERVED: AIRPORT ID		CITY			STATE
KCLM		PORT ANGELES	WA		
COMMUNICATIONS: CHART: SEA FSS, CTAF					
FIXES AND/OR NAVAIDS: YYJ VOR/DME, SEA VORTAC					
REMARKS: LETTER OF APPROVAL ON FILE PERMITTING RWY 9 CEILING AND VISIBILI ABBREVIATED AMENDMENT.	TY MINIMUMS IN	N LIEU OF STANDARD MINIM	UMS. CLIMB GRADIENT D	SAPPROVED BY AFS.	
FLIGHT INSPECTED BY SIGNATURE	Digitali	ly signed by	OFFICE	DATE	
Processed IAW Technical Support Group (AJF-17) Memo dated 07/07/2021, Subject: Guidance for Procedural Changes Requiring Flight Inspection/Validation.		VIE BAKER 12, 2023			
DEVELOPED BY Digitally signed by SIGNATURE			OFFICE	DATE	
SCOTT E. LINDHOLM JOHNNIE BAKER Jul 12, 2023			AJV-A431	03/31/2023	
APPROVED BY Digitally signed by SIGNATURE			OFFICE	DATE	TITLE
ERIC N. SUSKI JOHNNIE BAKER			AJV-A431		MANAGER
Jul 12, 2023 REQUIRED EFFECTIVE DATE ROUTINE					
COORDINATED WITH:					
	OTHER: ARI	PT MGR, NUW APP CON, SEA	A FSS, ZEA.		
CHANGES - REASONS: 1. CHANGED RWYS 8/26 TO 9/27 TRUE BEARING OF AFFECTED RUNWAY 2. MOVED ADF REQUIRED NOTE FROM PROCEDURAL DATA NOTES TO EC	OVALITZ 20 CHECKER				

DP NAME	NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	ACTUAL EFFECTIVE DATE
WATTR	EIGHT	WATTR8.WATTR	SEVEN	7/19/2018	25 JANUARY 2024
3 ADDED "ABBREVIATED AMENDMENT" TO REMARKS - IAW FAAO 82	60 46.I APPENDIX D	SECTION 2 PARAGRAPH Q3			

8260.46J APPENDIX D, SECTION 2, PARAGRAPH

4. REMOVED APA FROM COORDINTATED WITH LINE - AMERICAN AIRLINES DOES NOT SERVE KCLM.

5. ADDED MSA "MSA FROM KCLM, 9000" - IAW FAAO 8260.46K APPENDIX E, SECTION 2, PARAGRAPGH K.

6. REMOVED VCOA AND UPDATED RWY 13 TAKEOFF MINIMUMS FROM "STANDARD WITH MINIMUM CLIMB OF 475 FT PER NM TO 1100 OR 3300-3 FOR VCOA" TO "NA - OBSTACLES" - PER ATC REQUEST.

