

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: WATMO CLIMB TO 1500 THEN CLIMBING RIGHT TURN TO 3900 DIRECT ZOXP AND HOLD. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 559 TREE 644347N/1580446W CHART CIRCLING ICON. CHART PROFILE NOTE: VISUAL SEGMENT - OBSTACLES. CHART PLANVIEW NOTE: FINAL APPROACH COURSE OFFSET 14.92 DEGREES CHART GALENA AWOS-3. FAC CROSSES RWY C/L EXTENDED 3000 FT FROM THLD.					
JUKEL (IAF)		ZOXP (NOPT) (TF) (FB) (RNP 1.00)		284.18 / 10.00				3900							
HESTS (IAF)		ZOXP (NOPT) (TF) (FB) (RNP 1.00)		103.56 / 10.00				3900							
ZOXP (IF/IAF)		LEBTE (TF) (FB) (RNP 1.00)		013.87 / 7.70				2100							
LEBTE (FAF)		WATMO (MAP) (TF) (FO) (RNP 0.30)		014.00 / 4.85											
WATMO (MAP)		1500 MSL		014.00				1500							
1500 MSL		ZOXP (DF) (FO) (RNP 1.00)						3900							
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S ZOXP, RT, 013.87 INBOUND, 3900 FT. IN LIEU OF PT (IAF) 3. FAC: 014.00 FAF: LEBTE _____ DIST FAF TO MAP: 4.85 THLD: 5.33 4. MIN. ALT: ZOXP 3900, LEBTE 2100 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: _____										MAG VAR: 13E		EPOCH YEAR: 2020			
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		X					
CATEGORY ==>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	920	1	522	920	1	522	920	1 1/2	522	920	1 1/2	522			
CIRCLING	1280	1 1/4	874	1380	1 1/2	974	1420	3	1014	1620	3	1214			
NOTES: CHART NOTE: RWY 3 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: USE GALENA ALTIMETER SETTING.															
CITY AND STATE NULATO, AK		ELEVATION: 406 TDZE: 398 AIRPORT NAME: NULATO		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 3, AMDT 1 5 JANUARY 2017				SUP: RNAV (GPS) RWY 2					
										AMDT: ORIG					
										DATED 11/25/2004					



RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: WATMO CLIMB TO 1500 THEN CLIMBING RIGHT TURN TO 3900 DIRECT ZOXP AND HOLD. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 559 TREE 644347N/1580446W CHART CIRCLING ICON. CHART PROFILE NOTE: VISUAL SEGMENT - OBSTACLES. CHART PLANVIEW NOTE: FINAL APPROACH COURSE OFFSET 14.92 DEGREES CHART GALENA AWOS-3. FAC CROSSES RWY C/L EXTENDED 3000 FT FROM THLD.					
JUKEL (IAF)		ZOXP (NOPT) (TF) (FB) (RNP 1.00)		284.18 / 10.00				3900							
HESTS (IAF)		ZOXP (NOPT) (TF) (FB) (RNP 1.00)		103.56 / 10.00				3900							
ZOXP (IF/IAF)		LEBTE (TF) (FB) (RNP 1.00)		013.87 / 7.70				2100							
LEBTE (FAF)		WATMO (MAP) (TF) (FO) (RNP 0.30)		014.00 / 4.85											
WATMO (MAP)		1500 MSL		014.00				1500							
1500 MSL		ZOXP (DF) (FO) (RNP 1.00)						3900							
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S ZOXP, RT, 013.87 INBOUND, 3900 FT. IN LIEU OF PT (IAF) 3. FAC: 014.00 FAF: LEBTE _____ DIST FAF TO MAP: 4.85 THLD: 5.33 4. MIN. ALT: ZOXP 3900, LEBTE 2100 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: _____										MAG VAR: 13E		EPOCH YEAR: 2020			
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		X					
CATEGORY ==>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	920	1	522	920	1	522	920	1 1/2	522	920	1 1/2	522			
CIRCLING	1280	1 1/4	874	1380	1 1/2	974	1420	3	1014	1620	3	1214			
NOTES: CHART NOTE: RWY 3 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: USE GALENA ALTIMETER SETTING.															
CITY AND STATE NULATO, AK		ELEVATION: 406 TDZE: 398 AIRPORT NAME: NULATO		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 3, AMDT 1 5 JANUARY 2017				SUP: RNAV (GPS) RWY 2					
										AMDT: ORIG					
										DATED 11/25/2004					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	284/30 CW 014/30 (NOPT)	284/10 CW 014/10	5100
2.	284/10 CW 014/10	ZOXOP (IF/IAF) (FB)	3900
3.	014/30 CW 104/30 (NOPT)	014/5 CW 104/5	6300
4.	014/5 CW 104/5	ZOXOP (IF/IAF) (FB)	3900
5.	104/30 CW 194/30	HESTS (IAF) (FB)	5500
6.	194/30 CW 284/30	JUKEL (IAF) (FB)	5000

QUALITY
20
CHECKED

CITY AND STATE NULATO, AK	ELEVATION: 406 TDZE: 398 AIRPORT NAME: NULATO	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 3, AMDT 1 5 JANUARY 2017	SUP: RNAV (GPS) RWY 2
				AMDT: ORIG
				DATED: 11/25/2004

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	284/30 CW 014/30 (NOPT)	284/10 CW 014/10	5100
2.	284/10 CW 014/10	ZOXOP (IF/IAF) (FB)	3900
3.	014/30 CW 104/30 (NOPT)	014/5 CW 104/5	6300
4.	014/5 CW 104/5	ZOXOP (IF/IAF) (FB)	3900
5.	104/30 CW 194/30	HESTS (IAF) (FB)	5500
6.	194/30 CW 284/30	JUKEL (IAF) (FB)	5000

QUALITY
20
CHECKED

CITY AND STATE NULATO, AK	ELEVATION: 406 TDZE: 398 AIRPORT NAME: NULATO	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 3, AMDT 1 5 JANUARY 2017	SUP: RNAV (GPS) RWY 2
				AMDT: ORIG
				DATED: 11/25/2004

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.



CITY AND STATE NULATO, AK	ELEVATION: 406	TDZE: 398	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 3, AMDT 1 5 JANUARY 2017	SUP: RNAV (GPS) RWY 2
	AIRPORT NAME: NULATO				AMDT: ORIG
					DATED: 11/25/2004