

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

VOR

STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - FAR PART 97, 23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP:
R-050 AKO VORTAC CW (IAF)	GERON AKO R-110/10 DME (No-PT)	10 DME ARC	6000	1.7 MI. AFTER AKO VORTAC OR AT 1.7 DME
R-170 AKO VORTAC CCW (IAF)	GERON (NoPT)	10 DME ARC	6000	CLIMBING RIGHT TURN TO 6000 DIRECT AKO VORTAC AND HOLD.
GERON (IAF)	AKO VORTAC (NoPT)	290/10	5200	
THIS IS A CORRECTED COPY OF A PROCEDURE PUBLISHED IN TL 92-6				ADDITIONAL FLIGHT DATA: HOLD E, RT, 290 INBOUND FAS OBST: 4854 GRAIN ELEV. 400926/1031214

1. PT L SIDE OF COURSE 110 OUTBOUND 6000 FT WITHIN 10 MILES OF AKO VORTAC (IAF)
- 2.
3. FAC: 289 FAF: AKO VORTAC DIST FAF TO MAP: 1.7 THLD: 1.7
4. MIN. ALT: AKO VORTAC 5200
5. MSA FROM: AKO VORTAC 5500

MAG VAR: 13E EPOCH YEAR: 85

MINIMUMS

TAKEOFF:	☒ STANDARD	SEE FAA FORM 8260-15 FOR THIS AIRPORT						ALTERNATE: NA		STANDARD					
CATEGORY	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
29	5120	1	439	5120	1	439	5120	1 1/4	439	5120	1 1/2	439			
CLING	5160	1	446	5180	1	466	5300	1 1/2	586	5300	2	586			

NOTES:

OBTAIN LOCAL ALTIMETER ON CTAF. IF NOT RECEIVED PROCEDURE NA.

CITY AND STATE	ELEVATION: <u>4714</u> TDZE: <u>4681</u>	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP	NONE
<u>AKRON, CO</u>	AIRPORT NAME: <u>AKRON-WASHINGTON CO</u>	<u>AKO</u>	<u>30 APR 92</u>	AMDT:	
			<u>VOR RWY 29, ORIG</u>	DATED:	