

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> KPWK	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 30	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>CITY</u> CHICAGO/PROSPECT HEIGHTS/WHEELING	<u>STATE</u> IL		
<u>AIRPORT ELEVATION</u> 647	<u>TDZE</u> 644	<u>SUPERSEDED</u>	<u>ORIGINAL/AMENDMENT</u> NONE	<u>DATED</u>	<u>MAG VAR</u> 2W	<u>EPOCH YEAR</u> 2000
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 30 NOVEMBER 2023	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
THORR	IAF	GENAZ		TF	FB	1.00	235.70	5.85	2500
GENAZ	IF	DUSTY		TF	FB	1.00	278.11	4.24	2200
DUSTY	FAF	RW30	MAP	TF	FO	0.30	300.03	4.76	
RW30	MAP	1047 MSL		CA			300.03		
1047 MSL		HIGUH		DF	FO	1.00			2500

MISSED APPROACH

MAP:

LNAV: RW30

MISSED APPROACH INSTRUCTIONS:

CLIMBING RIGHT TURN TO 2500 DIRECT HIGUH AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:



COORDINATED WITH:

A4A ☐ ALPA ☒ AOPA ☒ APA ☐ HAI ☐ NBAA ☒ OTHER: ORD APP CTL, PWK ATCT, AMGER

<u>FLIGHT CHECKED BY</u> SCOTT WIEBE	<i>Digitally signed by</i> CASIMIR L TABAKA Sep 25, 2023	<u>OFFICE</u> FPO	<u>DATE</u> 09/22/2023	
<u>DEVELOPED BY</u> CASIMIR L. TABAKA (JON NEIDIGH)	<i>Digitally signed by</i> CASIMIR L TABAKA Jul 10, 2023	<u>OFFICE</u> AJV-A432	<u>DATE</u> 10/05/2023	
<u>APPROVED BY</u> JOHNNIE BAKER	<i>Digitally signed by</i> CASIMIR L TABAKA Jul 10, 2023	<u>OFFICE</u> AJV-A430	<u>DATE</u> 10/05/2023	<u>TITLE</u> MANAGER

