

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
SILENT	THREE	SLNT3.REBAS	TWO	05/21/2020	08SEPT2022
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
☐	☐	☒	☐	☐	☐

DP ROUTE DESCRIPTION:

TAKEOFF RUNWAY 30: CLIMBING LEFT TURN ON HEADING 270.00 TO V87 (COMMENCE RIGHT TURN AT SFO R-360) TO REBAS INT/SFO 19.26 DME. CROSS REBAS INT AT OR ABOVE 6000. THENCE...

...(TRANSITION). EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
MENDOCINO	SLNT3.ENI	REBAS INT	SASSU INT/SFO 44.86 DME	342.00 (SFO R-342)	25.61	8000	5000	
		SASSU INT	ENI VORTAC	298.43 (ENI R-118)	58.40	8000	5900	
RED BLUFF	SLNT3.RBL	REBAS INT	SAWNA INT/SFO 74.87 DME	342.00 (SFO R-342)	55.62	8000	5300	
		SAWNA INT	RBL VORTAC	348.00 (RBL R-168)	74.16	8000	5400	
SACRAMENTO	SLNT3.SAC	REBAS INT	SAC VORTAC	035.80 (SAC R-216)	49.58	3000		
LINDEN	SLNT3.LIN	REBAS INT	LIN VOR/DME	066.43 (LIN R-246)	65.92	5000		

PROCEDURAL DATA NOTES:**PBN REQUIREMENTS NOTES:****EQUIPMENT REQUIREMENT NOTES:****TAKEOFF MINIMUMS:**

RWY 10L, 10R, 12, 15, 28L, 28R, 33: NA - ATC

RWY 30: STANDARD WITH MINIMUM CLIMB OF 405 FT PER NM TO 6000

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:**MSA:**

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
SILENT	THREE	SLNT3.REBAS	TWO	05/21/2020	08SEPT2022

LOST COMMUNICATIONS PROCEDURES:**ADDITIONAL FLIGHT DATA:**

CHART: TOP ALTITUDE: ASSIGNED BY ATC

CHART: V87, V150

CHART: SFO R-360

AIRPORTS SERVED:

<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>
KOAK	OAKLAND	CA

COMMUNICATIONS:

CHART ATIS, CLNC DEL

FIXES AND/OR NAVAIDS:

CHART: OAK VOR/DME

REMARKS:

WESTERN MOUNTAINOUS TERRAIN REDUCTION APPLIED TO SACRAMENTO (SAC) TRANSITION.

SILENT THREE AMENDMENT DOES NOT SATISFY PERIODIC REVIEW REQUIREMENTS.

ABBREVIATED AMENDMENT.

FLIGHT INSPECTED BY

PROCESSED IAW TECHNICAL SUPPORT GROUP (AJF-17) MEMO DATED 07/07/2021 GUIDANCE
FOR PROCEDURAL CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION.

*Digitally signed by***DONALD E SMITH**

May 19, 2022

OFFICE**DATE****DEVELOPED BY**

STEVEN WINNER *Digitally signed by*
STEVEN E WINNER
May 02, 2022

OFFICE**DATE**

AJV-A413

03/24/2022

APPROVED BY

JULIE MORGAN

*Digitally signed by***DONALD E SMITH**

May 19, 2022

OFFICE**DATE****TITLE**

AJV-A410

MANAGER

REQUIRED EFFECTIVE DATE

ROUTINE

COORDINATED WITH:

A4A ☒ **ALPA** ☒ **AOPA** ☒ **APA** ☒ **HAI** ☐ **NBAA** ☒ **OTHER:** ZOA, NORCAL APP CON, OAK ATC, AMGR

CHANGES - REASONS:

1. CHANGED DP ROUTE DESCRIPTION FROM "CLIMBING LEFT TURN HEADING..." TO "CLIMBING LEFT TURN ON HEADING..." - UPDATED CRITERIA.
2. ADDED RWY 28R TO "NA - ATC" RUNWAYS AND CORRECTED FORMATTING. - CORRECTION TO PREVIOUS AMENDMENT AND CLEARS NOTAM FDC 2/8029.
3. DELETED "IAW 8260.3D SEC 15-2-1" FROM MOUNTAINOUS TERRAIN REDUCTION REMARK. - IN ORDER TO KEEP REMARK VALID IN CASE OF FUTURE CRITERIA VERSION CHANGES.
4. CHANGED VERSION FROM TWO TO THREE IN PERIODIC REVIEW REMARK. - UPDATED REMARK TO CURRENT NUMBER.
5. ADDED ABBREVIATED AMENDMENT TO REMARKS. - ABBREVIATED AMENDMENT ACCOMPLISHED TO CLEAR FDC 2/8029.
6. ADDED "CHART" AND REMOVED NORCAL DEP CON FROM COMMUNICATIONS. - UPDATED CRITERIA.
7. MOVED "RWY 10L, 10R, 12, 15, 28L, 28R, 33: NA - ATC" AND "RWY 30: STANDARD WITH MINIMUM CLIMB OF 405 FT PER NM TO 6000" FROM PROCEDURAL DATA NOTES TO TAKEOFF MINIMUMS. - IAW 8260.46H.

QUALITY
21
CHECKED