

U.S. Department of Transportation
Federal Aviation Administration

**RNAV-STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE		
HANER WP (IAF)	GIRDE WP (NO PT) (TF) (FB)	087.39/5.00	3000	LNAV: RW36	
JALMU WP (IAF)	GIRDE WP (NO PT) (TF) (FB)	267.53/5.00	3000	CLIMB TO 2000 THEN CLIMBING LEFT TURN TO 3000 DIRECT GIRDE WP AND HOLD.	
GIRDE WP (IF/IAF)	FILIG WP (TF) (FB)	357.46/5.75	2600		
RW36 (MAP)	GIRDE WP (DF) (FO)		3000	ADDITIONAL FLIGHT DATA: FAS OBST: 1029 TREES 403948 / 922618 FILIG WP TO RW36: 3.00/40	

- PT NA SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)
- HOLD S GIRDE WP, LT, 357.46 INBOUND, 3000 FT IN LIEU OF PT (IAF)
- FAC: 357.46 FAF: FILIG WP _____ DIST FAF TO MAP: _____ THLD: 5.25
- MIN. ALT: GIRDE WP 3000; FILIG WP 2600
- DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____
- MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____
- GS ANGLE: _____ TCH: _____ 34:1 IS CLEAR
- MSA FROM: _____

CHART: TDZE 888

FINAL SEGMENT: (TF)

MAG VAR: 2E

EPOCH YEAR: 00

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15 FOR THIS AIRPORT	ALTERNATE: N	A	X										
CATEGORY	A			B			C			D			E			
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	
LNAV	MDA	1340	1	452	1340	1	452	1340	1 1/4	452		NA				
CIRCLING		1440	1	552	1440	1	552	1520	1 3/4	632		NA				

NOTES:
USE OTTUMWA ALTIMETER SETTING; WHEN NOT AVAILABLE, PROCEDURE NA.
GPS OR RNP-0.3 REQUIRED. DME/DME RNP-0.3 NA.

CITY AND STATE	ELEVATION: 888 TDZE: 888	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
BLOOMFIELD, IA	AIRPORT NAME: BLOOMFIELD MUNI	RNAV	APR 18 2002 RNAV (GPS) RWY 36, ORIG	AMDT: NONE
				DATED

RNAV

STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - FAR PART 97. 33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA:

FROM	TO	ALTITUDE
1. 268/30 CW 087/30	GIRDE (IF/IAF) (NO PT)	3000
2. 087/30 CW 177/30	HANER (IAF)	3000
3. 177/30 CW 268/30	JALMU (IAF)	3000

CITY AND STATE BLOOMFIELD, IA	ELEVATION: 888 TDZE: 888	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: APR 18 2002 RNAV (GPS) RWY 36, ORIG	SUP:
	AIRPORT NAME: BLOOMFIELD MUNI			AMDT: NONE
	DATED:			