U.S. Department of Transportation

Federal Aviation Administration

**Transmittal Letter 21-12** 

**April 16, 2021** 

## PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
5/20/2021	AR	Walnut Ridge	Walnut Ridge Rgnl	1/2790	4/1/2021	RNAV (GPS) RWY 18, Amdt 1A

## AIRAC Date: 20 MAY 2021

FDC 1/2790 ARG IAP WALNUT RIDGE RGNL, WALNUT RIDGE, AR. RNAV (GPS) RWY 18, AMDT 1A... CIRCLING CAT C MDA 800/HAA 521, CIRCLING CAT D MDA 1000/HAA 721, VIS CAT D 2 1/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JONESBORO ALTIMETER SETTING AND INCREASE LPV DA TO 529 FEET, LNAV/VNAV DA TO 579 FEET, AND ALL MDAS 60 FEET; INCREASE CIRCLING CAT D VISIBILITY 1/4 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4 - NA WHEN LOCAL WEATHER NOT AVAILABLE. DELETE NOTE: FOR INOPERATIVE ODALS, INCREASE LPV ALL CATS AND LNAV/VNAV ALL CATS VISIBILITY TO 1 MILE AND LNAV CAT C AND D VISIBILITY TO 1 1/8 MILE. THIS IS RNAV (GPS) RWY 18, AMDT 1B. 2103311447-PERM