

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION															
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LP: RW18 LNAV: RW18 CLIMBING LEFT TURN TO 3500 DIRECT DLL VORTAC AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 261.00 INBOUND. CHART FAS OBST: 1263 TREE 433330N/0895902W WAAS CHANNEL # 78427 REFERENCE PATH ID: W18A TUSME TO RW18: 3.00/50. CHART BARABOO AWOS. LTP HAE: 240.7 M											
FAPKO (IAF)	ZETSU (NOPT) (FB)	089.19 / 18.85	3500												
ZETSU (IF/IAF)	TUSME (FB)	150.45 / 7.00	2500												
TUSME (FAF)	UQRIK/2.60 NM TO RW18 (FB)	180.50 / 2.25													
UQRIK/2.60 NM TO RW18	RW18 (MAP) (FO)	180.50 / 2.60													
RW18 (MAP)	1306 MSL	180.50													
1306 MSL	DLL VORTAC (FO)		3500												
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)															
2. HOLD NW ZETSU, RT, 150.45 INBOUND, 3500 FT. IN LIEU OF PT (IAF)															
3. FAC: <u>180.50</u> FAF: <u>TUSME</u> DIST FAF TO MAP: <u>4.85</u> THLD: <u>4.85</u>															
4. MIN. ALT: ZETSU 3500, TUSME 2500, UQRIK/2.60 NM TO RW18 1780															
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u>150</u> HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>															
6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u>															
7. GS ANGLE: <u> </u> TCH: <u>34:1</u> IS NOT CLEAR															
8. MSA FROM: RW18 3300				MAG VAR: 0E EPOCH YEAR: 1985											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X											
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	1560	1	655	1560	1	655		NA			NA				
LNAV MDA	1580	1	675	1580	1	675		NA			NA				
CIRCLING	1600	1	694	1600	1	694		NA			NA				
NOTES: CHART NOTE: USE BARABOO ALTIMETER SETTING; WHEN NOT RECEIVED, USE LONE ROCK ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 906 THRE: 905		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
REEDSBURG, WI		AIRPORT NAME: REEDSBURG MUNI		RNAV		RNAV (GPS) RWY 18, ORIG 05 APR 2012				AMDT: NONE					
												DATED			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT FAPKO ON V82-170-510 WESTBOUND.

QUALITY
CHECKED

CITY AND STATE REEDSBURG, WI	ELEVATION: 906 AIRPORT NAME: REEDSBURG MUNI	THRE: 905	FACILITY IDENTIFIER: RNAV	PROCEDURE NO / AMDT NO / EFFECTIVE DATE: RNAV (GPS) RWY 18, ORIG 05 APR 2012	SUP:
					AMDT: NONE
					DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	C35
RUNWAY	RW18
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	0
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W18A
LTP/FTP LATITUDE	433150.0525N
LTP/FTP LONGITUDE	0895855.9345W
LTP/FTP ELLIPSOIDAL HEIGHT	+02407
FPAP LATITUDE	433020.9400N
FPAP LONGITUDE	0895857.0000W
THRESHOLD CROSSING HEIGHT (TCH)	00050.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1408
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0

CRC REMAINDER

6DED07EB

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+02757
FPAP ORTHOMETRIC HEIGHT	+02757

CITY AND STATE

REEDSBURG, WI

ELEVATION: 906

THRE: 905

AIRPORT NAME:

REEDSBURG MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 18, ORIG

05 APR 2012

SUP:

AMDT: NONE

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

CITY AND STATE REEDSBURG, WI	ELEVATION: 906 THRE: 905 AIRPORT NAME: REEDSBURG MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, ORIG 05 APR 2012	SUP:
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

ELEVATION: 906 THRE: 905
AIRPORT NAME:
REEDSBURG MUNI

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 18, ORIG
05 APR 2012

SUP:	
AMDT:	NONE
DATED:	