

PREPARED BY THE PRODUCT SUPPORT GROUP, AJV-34

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
20 Oct 11	IL	Springfield	Abraham Lincoln Capital	1/1063	8/19/11	RNAV (GPS) RWY 22, Orig

FDC **1/1063** SPI FI/P IAP ABRAHAM LINCOLN CAPITAL, SPRINGFIELD, IL. RNAV (GPS) RWY 22, ORIG... LPV DA 884 ALL CATS. LNAV/VNAV DA 1050/HAT 452, VISIBILITY ALL CATS 1 MILE. LNAV HAT 382 ALL CATS, LNAV CAT C/D VISIBILITY 5/8. CIRCLING CATS A/B/C MDA 1160/HAA 562, CAT D HAA 602. CHANGE LOCAL ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LINCOLN ALTIMETER SETTING AND INCREASE ALL DA 57 FEET, ALL MDA 60 FEET, AND INCREASE LNAV/VNAV ALL CATS, LNAV CATS C/D AND CIRCLING CAT C VISIBILITY 1/4 MILE. CHANGE INOPERATIVE MALSR NOTE TO READ: FOR INOPERATIVE MALSR INCREASE LPV ALL CATS VISIBILITY TO 1 MILE. CHART NOTE: FOR INOPERATIVE MALSR WHEN USING LINCOLN ALTIMETER SETTING INCREASE LPV ALL CATS VISIBILITY TO 1 1/8, LNAV/VNAV ALL CATS VISIBILITY TO 1 3/4, LNAV CATS C/D VISIBILITY TO 1 1/4. CHANGE NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING LINCOLN ALTIMETER SETTING. CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS LNAV/VNAV NA BELOW -16C (4F) AND ABOVE 47C (116F). CHART APT ELEV AND THRE 598. CHART FAS OBSTACLE 712 MSL TOWER 355253.45N-0893746.36W . THIS IS RNAV (GPS) RWY 22, ORIG-A.