

**Federal Aviation
Administration**

Transmittal Letter 19-05

January 11, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
28-Feb-19	NC	Goldsboro	Wayne Executive Jetport	8/3791	1/8/19	RNAV (GPS) RWY 23, Amdt 1A

AIRAC Date: 28 FEBRUARY 2019

FDC **8/3791** GWW IAP WAYNE EXECUTIVE JETPORT, Goldsboro, NC. RNAV (GPS) RWY 23, AMDT 1A... LPV VIS 3/4 SM ALL CATS. PBN REQUIREMENTS NOTE: RNP APCH. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SMITHFIELD ALTIMETER SETTING AND INCREASE LPV DA TO 387 FT, LNAV/VNAV DA TO 499 FT AND ALL MDA 60 FEET; INCREASE LNAV/VNAV VIS ALL CATS TO 1 SM AND LNAV VIS CATS C/D TO 1 1/8. CHART NOTE: FOR INOPERATIVE ALS WHEN USING SMITHFIELD ALTIMETER SETTING, INCREASE LNAV/VNAV VIS ALL CATS TO 1 SM, LNAV VIS CATS A/B TO 1 SM AND CATS C/D TO 1 3/8 SM. DELETE NOTE DME/DME RNP-0.3 NA. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SMITHFIELD ALTIMETER SETTING AND INCREASE LPV DA TO 387 FT, LNAV/VNAV DA TO 499 FT AND ALL MDA 60 FEET; INCREASE LNAV/VNAV ALL CATS AND LNAV CATS C AND D D TO 1 1/8 MILE. DELETE NOTE: FOR INOPERATIVE ODALS, INCREASE LNAV/VNAV CAT A/B/C VISIBILITY TO 1 MILE, LNAV CAT C TO 1 1/8 MILE. THIS IS RNAV (GPS) RWY 23, AMDT 1B. 1812202211-PERM