

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
LOGNE (IAF)	USUPE (NOPT) (FB)	089.49 / 5.00	2100	LNAV: RW35
NEGNE (IAF)	USUPE (NOPT) (FB)	269.61 / 5.00	2100	CLIMB TO 2500 DIRECT IMUDE AND HOLD.
USUPE (IF/IAF)	ITOXE (FB)	359.55 / 6.01	1800	
				ADDITIONAL FLIGHT DATA: HOLD N, RT, 179.55 INBOUND. CHART FAS OBST: 313 TREE 350714N/0901407W ITOXE TO RW35: 3.04/40.

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD S USUPE, RT, 359.55 INBOUND, 2100 FT. IN LIEU OF PT (IAF)
3. FAC: 359.55 FAF: ITOXE DIST FAF TO MAP: 4.80 THLD: 4.80
4. MIN. ALT: USUPE 2100, ITOXE 1800
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: 34:1 IS NOT CLEAR
8. MSA FROM:

MAG VAR: 1E EPOCH YEAR: 1995

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @										
CATEGORY	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	580	1	368	580	1	368	580	1	368	580	1 1/4	368			
CIRCLING	620	1	408	680	1	468	680	1 1/2	468	780	2	568			

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA. @ NA WHEN LOCAL WEATHER NOT AVAILABLE.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MEMPHIS INTL ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET INCREASE LNAV CATS C AND D VISIBILITY 1/4 MILE.




CITY AND STATE WEST MEMPHIS, AR	ELEVATION: 212 TDZE: 212 AIRPORT NAME: WEST MEMPHIS MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, ORIG 11 FEB 2010	SUP: AMDT: NONE DATED
------------------------------------	--	------------------------------	--	-----------------------------

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	<u>FROM</u>	<u>TO</u>	<u>ALT</u>
1.	270/30 CW 089/30 (NOPT)	USUPE (IF/IAF) (FB)	2100
2.	089/30 CW 180/30	LOGNE (IAF) (FB)	2500
3.	180/30 CW 270/30	NEGNE (IAF) (FB)	2500



CITY AND STATE WEST MEMPHIS, AR	ELEVATION: 212 TDZE: 212 AIRPORT NAME: WEST MEMPHIS MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, ORIG 11 FEB 2010	SUP:
				AMDT: NONE
				DATED:

