

FLIGHT STANDARDS SERVICE - FAR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
HOPUN INT (IF/IAF)	POM VORTAC (NOPT)	074.00 / 6.25	3700	MAP: 5.05 MILES AFTER POM VORTAC OR AT POM 5.05 DME FIX CLIMBING RIGHT TURN TO 4000 VIA HEADING 105 AND PDZ R-315 TO PDZ VORTAC AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 258.00 INBOUND. CHART FAS OBST: 1699 TREE 340744N/1174208W POM VORTAC TO RW06: 4.22/40.

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. **HOLD SW POM VORTAC, RT, 053.00 INBOUND, 3700 FT. IN LIEU OF PT (IAF)**
3. FAC 053.08 FAF POM VORTAC DIST FAF TO MAP 5.05 THLD
4. MIN. ALT POM VORTAC 3700
8. MSA FROM: **POM VORTAC 070-160 7000, 160-250 3600, 250-070 11300**

EPOCH YEAR:1975

MINIMUMS

[illegible]

NOTES:

CHART NOTE: CIRCLING NA NORTH OF RWY 06/24.
CHART NOTE: USE ONTARIO ALTIMETER SETTING.

CITY AND STATE UPLAND, CA	ELEVATION: 1444 TDZE: AIRPORT NAME: CABLE	FACILITY IDENTIFIER: POM	PROCEDURE NO./AMD'T NO./EFFECTIVE DATE: VOR-A, ORIG 15 JAN 2009	SUP	
				AMDT	NONE
				DATE	