

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: AJHUD/TWF 0.90 DME
YUSUN/TWF 11.00 DME CW (IAF)	TIRAE/TWF 11.00 DME	11.00 DME ARC	6600	CLIMBING LEFT TURN TO 6000 ON HEADING 245 AND TWF R-314 TO WALIL/TWF 11.00 DME AND HOLD.
WALIL/TWF 11.00 DME CCW (IAF)	TIRAE/TWF 11.00 DME	11.00 DME ARC	6000	
TIRAE/TWF 11.00 DME (IF)	LUVIY/TWF 4.80 DME	077.80 / 6.20 (TWF R-258)	5500	
				ADDITIONAL FLIGHT DATA: HOLD SE, RT, 313.99 INBOUND. CHART FAS OBST: 4306 POLE 422751N/1143057W OBST: 4509 AAO 422805N/1143633W CHART VDP AT 1.74 DME; DISTANCE VDP TO THLD 1.13 MILES. CHART TWF R-314 AT WALIL. CHART TWF R-177 AT YUSUN. LUVIY TO RW8: 2.83/58. CHART CIRCLING ICON. FAC CROSSES RWY C/L EXTENDED 1718 FROM THLD.

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. PROFILE STARTS AT TIRAE/TWF 11.00 DME
3. FAC 077.80 FAF LUVIY/TWF 4.80 DME DIST FAF TO MAP THLD 4.18
4. MIN. ALT TIRAE 6000, LUVIY 5500, ETWED/TWF 2.50 DME 4760
8. MSA FROM: TWF VORTAC 040-150 9300, 150-240 8800, 240-040 6200

MAG VAR: 18E EPOCH YEAR: 1965

MINIMUMS

TAKEOFF: CATEGORY =====>	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-8	4560	1	416	4560	1	416	4560	1 1/8	416	4560	1 1/8	416			
CIRCLING	4700	1	546	4780	1	626	5100	2 3/4	946	5100	3	946			

NOTES:

CHART NOTE: CIRCLING TO RWY 30 NA AT NIGHT.
 CHART NOTE: VDP NA WITH JEROME ALTIMETER SETTING.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JEROME ALTIMETER SETTING AND INCREASE ALL MDA 60FT AND S-8 CATS C AND D VISIBILITY 1/4 MILE AND CIRCLING CAT C VISIBILITY 1/4 MILE.

@ CAT C 1000-2 3/4, CAT D 1000-3.
 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.



CITY AND STATE TWIN FALLS, ID	ELEVATION: 4154 THRE: 4144	FACILITY IDENTIFIER: TWF	PROCEDURE NO/AMDT NO/EFFECTIVE DATE: VOR/DME RWY 8, AMDT 1 17 OCTOBER 2013	SUP VOR/DME RWY 7
	AIRPORT NAME: JOSLIN FIELD - MAGIC VALLEY RGNL			AMDT ORIG-A
	DATE 07/05/2007			

VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE TWIN FALLS, ID	ELEVATION: 4154 THRE: 4144 AIRPORT NAME: JOSLIN FIELD - MAGIC VALLEY RGNL	FACILITY IDENTIFIER: TWF	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME RWY 8, AMDT 1 17 OCTOBER 2013	SUP: VOR/DME RWY 7
				AMDT: ORIG-A
				DATED: 07/05/2007