

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> SLR	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 19	<u>ORIGINAL/AMENDMENT</u> ORIG-F	<u>CITY</u> SULPHUR SPRINGS	<u>STATE</u> TX
<u>AIRPORT ELEVATION</u> 489	<u>TDZE</u> 476	<u>SUPERSEDED</u> RNAV (GPS) RWY 19	<u>DATED</u> 11/03/2022	<u>EPOCH YEAR</u> 2010
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 21 MARCH 2024	<u>MAG VAR</u> 3E	<u>CANCEL/SUSPEND</u>
		<u>REQUIRED EFFECTIVE DATE</u> ROUTINE		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
MONTE		PIPIC		TF	FB	1.00	123.89	13.56	3000
LENYI		WUSNU		TF	FB	1.00	243.95	23.18	3000
PIPIC	IAF	WEDAT	NOPT	TF	FB	1.00	124.01	6.00	2500
WUSNU	IAF	WEDAT	NOPT	TF	FB	1.00	243.72	6.00	2500
PRX VOR/DME	IAF	WEDAT	NOPT	TF	FB	1.00	206.81	13.71	2500
WEDAT	IF/IAF	EVIJI		TF	FB	1.00	186.68	6.07	2000
EVIJI	FAF	ZILVA/1.80 NM TO RW19		TF	FB	0.30	186.67	2.89	
ZILVA/1.80 NM TO RW19		RW19	MAP	TF	FO	0.30	186.67	1.80	
RW19	MAP	726 MSL		CA			186.67		
726 MSL		EDDGR		DF	FO	1.00			3000

MISSED APPROACH

MAP:

LPV: DA
LNAV/VNAV: DA
LNAV: RW19

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 3000 DIRECT EDDGR AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

QUALITY
34
CHECKED

PROFILE:

1. PT

SIDE OF COURSE

OUTBOUND

FT WITHIN

MILES OF

(IAF)

2. HOLD N WEDAT, RT, 186.68 INBOUND, 2500 FT. IN LIEU OF PT (IAF), MAX 6000.

3. FAC: 186.67FAF: EVIJI

DIST FAF TO MAP: 4.69

DIST FAF TO THLD: 4.69

4. MIN ALT: WEDAT 2500, EVIJI 2000, ZILVA/1.80 NM TO RW19 1060

5. DIST TO THLD FROM OM:MM:IM:150 HAT:250 HAT: 0.69GS ANT:

6. MIN GP INCPT: 2000GP ALT AT PFAF : EVIJI 2000OM:MM:IM:

7. GP ANGLE: 3.0034:1: IS CLEAR20:1: IS CLEARTCH: 40.0

8. MSA FROM: RW19 2600

PBN REQUIREMENTS NOTE:

RNP APCH - GPS.

NOTES:

CHART NOTE: CIRCLING NA E OF RWY 1-19.
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15°C OR ABOVE 54°C.

ADDITIONAL FLIGHT DATA:

HOLD S, RT, 006.64 INBOUND.
CHART FAS OBST: 589 TREE 330958N/0953641W.
CHART VDP AT 1.05 NM TO RW19.
WAAS CHANNEL # 90323
REFERENCE PATH ID: W19A
CHART CIRCLING ICON.
LTP HAE: 115.8 M

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ STANDARD - NA WHEN LOCAL WEATHER NOT AVAILABLE.

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LPV DA	726	3/4	250	726	3/4	250	726	3/4	250		NA				
LNAV/VNAV DA	776	1	300	776	1	300	776	1	300		NA				
LNAV MDA	840	1	364	840	1	364	840	1	364		NA				
CIRCLING	940	1	451	940	1	451	1000	1 1/2	511		NA				



CHANGES - REASONS

1. INCORPORATED CHANGES FROM P-NOTAM FOR AMDT ORIG-E INTO FORM - IAW 8260.19I PARA 8-3-4.C (3).
2. REMOVED CHART PLANVIEW NOTE: "PROCEDURE NA FOR ARRIVAL AT PRX VOR/DME ON V583 NORTHBOUND" - V583 REMOVED FROM ENROUTE CHART.
3. REMOVED "*" FROM PROFILE LINE 4 - IAW WITH 8260.19I 1-1-5. F. (12).
4. ADDITIONAL FLIGHT DATA: REMOVED "*" FROM CHART VDP AT 1.05 NM TO RW19 AND LNAV ONLY - IAW WITH 8260.19I 1-1-5. F. (12).

COORDINATED WITH:

A4A☐ALPA☒AOPA☒APA☐HAI☐NBAA☒OTHER: ZFW, AMGR, STATE AERO

FLIGHT CHECKED BY

PROCESSED IAW TECHNICAL SUPPORT GROUP (AJF-17) MEMO DATED 07/07/2021 GUIDANCE FOR PROCEDURAL CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION

OFFICE

DATE

Digitally signed by

ROBERT G HAMILTON

Jan 23, 2024

DEVELOPED BY

DAVID TEFFETELLER (LANCE W. BELL)

Digitally signed by

ROBERT G HAMILTON

Jan 23, 2024

OFFICE

AJV-A433

DATE

08/02/2023

APPROVED BY

DAVID TEFFETELLER

Digitally signed by

ROBERT G HAMILTON

Jan 23, 2024

OFFICE

AJV-A430

DATE

TITLE

MANAGER



FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KSLR
RUNWAY	RW19
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W19A
LTP/FTP LATITUDE	330959.7770N
LTP/FTP LONGITUDE	0953711.1860W
LTP/FTP ELLIPSOIDAL HEIGHT	+01158
FPAP LATITUDE	330831.7715N
FPAP LONGITUDE	0953728.9900W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
CRC REMAINDER	71DAA0E1

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+01420
FPAP ORTHOMETRIC HEIGHT	+01420