

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION  
**TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
TRACY, MN	TRACY MUNI	13 JAN 2011	ORIG

**TAKEOFF MINIMUMS:**

RWY 6, 17, 24, 35, NA - ENVIRONMENTAL.

RWY 11 STANDARD.

RWY 29, 300-2 1/4 OR STANDARD WITH MINIMUM CLIMB OF 250 FEET PER NM TO 1800.

**TEXTUAL DEPARTURE PROCEDURES:**

**TAKEOFF OBSTACLE NOTES:**

NOTE: RWY 11, TREE 56 FT FROM DER, 174 FT RIGHT OF CENTERLINE, 20 FT AGL/1342 FT MSL, NUMEROUS TREES AND BUSHES BEGINNING 137 FT FROM DER, 86 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/1410 FT MSL. NOTE: RWY 29, TOWER 1.9 NM FROM DER, 1951 FT LEFT OF CENTERLINE, 265 FT AGL/1625 FT MSL.

**CONTROLLING OBSTACLES:**

RWY 29: 1625 MSL TOWER, 441540.00N-0953911.00W.

