

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW07 CLIMB TO 5600 DIRECT OKLUH AND HOLD, CONTINUE CLIMB-IN-HOLD TO 5600.CHART NOTE: ** MISSED APPROACH REQUIRES MINIMUM CLIMB GRADIENT OF 240 FEET PER NM TO 3400. ADDITIONAL FLIGHT DATA: HOLD NE, LT, 246.24 INBOUND. 2459 AAO 363452.00N/0831851.00W 1719 AAO 363754.00N/0831724.00W DISTANCE TO THLD FROM 250 HAT: 0.74 NM. CHART VDP AT 2.10 NM TO RW07* *LNAV ONLY. WAAS CHANNEL # 78430 REFERENCE PATH ID: W07A CHART CIRCLING ICON. LTP HAE: 385.5 M									
ZOKAP (IAF)		TILYU (NOPT) (TF) (FB) (RNP 1.00)			155.87 / 10.00			5700											
WIRVU (IAF)		TILYU (NOPT) (TF) (FB) (RNP 1.00)			335.99 / 10.00			5700											
TILYU (IF/IAF)		SACGO (TF) (FB) (RNP 1.00)			065.93 / 7.59			3400											
SACGO (FAF)		HONEB/3.00 NM TO RW07 (TF) (FB) (RNP 0.30)			066.01 / 3.26														
HONEB/3.00 NM TO RW07		RW07 (MAP) (TF) (FO) (RNP 0.30)			066.01 / 3.00					(SEE FORM 8260-10) THIS IS A CORRECTED COPY OF A PROCEDURE ORIGINALLY PUBLISHED IN TL 17-05.									
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD SW TILYU, RT, 065.93 INBOUND, 5700 FT. IN LIEU OF PT (IAF) 3. FAC: 066.01 FAF: SACGO DIST FAF TO MAP: 6.26 THLD: 6.26 4. MIN. ALT: TILYU 5700, SACGO 3400, HONEB/3.00 NM TO RW07 2360* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 3400 GS ALT AT: SACGO 3400 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS NOT CLEAR 8. MSA FROM: _____																MAG VAR: 6W		EPOCH YEAR: 2005	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @										
CATEGORY ==>		A			B			C			D			E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LPV DA **	1643	1	250	1643	1	250	1643	1	250		NA								
LPV DA	1881	1 3/4	488	1881	1 3/4	488	1881	1 3/4	488		NA								
LNAV/VNAV DA	2024	2 1/2	631	2024	2 1/2	631	2024	2 1/2	631		NA								
LNAV MDA	2080	1	687	2080	1	687	2080	1 3/4	687		NA								
CIRCLING	2140	1	729	2180	1	769	2600	3	1189		NA								
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: RWY 07 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.																@ NA WHEN LOCAL WEATHER NOT AVAILABLE. @ CAT C 1200-3			
CITY AND STATE JONESVILLE, VA		ELEVATION: 1411 TDZE: 1393 AIRPORT NAME: LEE COUNTY			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 7, AMDT 2 2 MARCH 2017					SUP:							
												AMDT: 1A							
												DATED 06/25/2015							



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW07 (MAP)	1643 MSL (CA)	066.01	

1643 MSL	OKLUH (DF) (FO) (RNP 1.00)	5600
----------	----------------------------	------

TAA

	FROM	TO	ALT
1.	336/30 CW 156/30 (NOPT)	TILYU (IF/IAF) (FB)	5700
2.	156/30 CW 246/30	156/10 CW 246/10	6000
3.	156/10 CW 246/10	ZOKAP (IAF) (FB)	5700
4.	246/30 CW 336/30	WIRVU (IAF) (FB)	5700

QUALITY
24
CHECKED

CITY AND STATE JONESVILLE, VA	ELEVATION: 1411	TDZE: 1393	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 7, AMDT 2 2 MARCH 2017	SUP:
	AIRPORT NAME:				AMDT: 1A
	LEE COUNTY				DATED: 06/25/2015

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	0VG
RUNWAY	RW07
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W07A
LTP/FTP LATITUDE	363902.3715N
LTP/FTP LONGITUDE	0831330.8500W
LTP/FTP ELLIPSOIDAL HEIGHT	+03855
FPAP LATITUDE	363946.8625N
FPAP LONGITUDE	0831154.8670W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 8FA05084

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K6
LTP ORTHOMETRIC HEIGHT	+04163
FPAP ORTHOMETRIC HEIGHT	+04163

QUALITY
24
CHECKED

CITY AND STATE JONESVILLE, VA	ELEVATION: 1411 TDZE: 1393 AIRPORT NAME: LEE COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 7, AMDT 2 2 MARCH 2017	SUP:
				AMDT: 1A
				DATED: 06/25/2015