

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97. 23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO			COURSE AND DISTANCE				ALTITUDE		MAP: 6.53 MILES AFTER EMI VORTAC						
											CLIMBING LEFT TURN TO 2900 DIRECT EMI VORTAC AND HOLD						
											ADDITIONAL FLIGHT DATA: FAS OBST: 1137 TOWER 393423/765815 EMI VORTAC TO RW34: 3.00/46 CHART VDP AT 4.46 DME DISTANCE VDP TO THLD 2.07 MILES CHART: AIRPORT ELEVATION : 789.2 RWY 34 TOUCHDOWN ZONE ELEVATION : 787.6						
1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF) 2. HOLD S EMI VORTAC, LT, 358.07 INBOUND, 2900 FT IN LIEU OF PT (IAF) 3. FAC 358.07 FAF EMI VORTAC DIST FAF TO MAP 6.53 THLD 6.53 4. MIN. ALT EMI VORTAC 2900 5. MSA FROM: EMI VORTAC 045-225 2600, 225-045 3400														MAG VAR: 8W		EPOCH YEAR: 65	
MINIMUMS																	
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15 FOR THIS AIRPORT				ALTERNATE: N A		STANDARD					
CATEGORY		A			B			C			D			E			
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA	
S-34		1480	1	692	1480	1	692	1480	2	692		NA					
CIRCLING		1480	1	691	1480	1	691	1480	2	691		NA					
NOTES:																	
CITY AND STATE				ELEVATION: 789 TDZE: 788				FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP			
WESTMINSTER, MD				CARROLL COUNTY REG/JACK B POAGE FIELD				EMI		VOR RWY 34, AMDT 4, 10/5/00				AMDT 3A			
														DATED 8/9/99			