

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
ROACH INT	SHY VOR/DME	143.36 / 12.40	2700
SGF VORTAC	SHY VOR/DME	036.11 / 53.83	3100
VIH VOR/DME	SHY VOR/DME	255.17 / 42.96	2700

MISSED APPROACH

MAP: 5.32 MILES AFTER SHY VOR/DME OR AT SHY 5.32 DME FIX

CLIMBING LEFT TURN TO 2700 DIRECT SHY VOR/DME AND HOLD.

ADDITIONAL FLIGHT DATA:
 CHART FAS OBST: 1005 TREE 380520N/0924129W
 SHY VOR/DME TO RW32: 3.19/40.

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD SE SHY VOR/DME, LT, 318.33 INBOUND, 2700 FT. IN LIEU OF PT (IAF)
- FAC 318.33 FAF SHY VOR/DME DIST FAF TO MAP 5.32 THLD 5.32
- MIN. ALT SHY VOR/DME 2700, ZOBGA/SHY 3.62 DME 1420*
- MSA FROM: SHY VOR/DME 3100

MAG VAR: 0E

EPOCH YEAR: 2015

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		X						
CATEGORY ==>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-32	1420	1	562	1420	1	562		NA			NA				
CIRCLING	1420	1	544	1420	1	544		NA			NA				

ZOBGA FIX MINIMUMS (DME REQUIRED)

S-32	1280	1	422	1280	1	422		NA			NA				
CIRCLING	1400	1	524	1400	1	524		NA			NA				

NOTES:

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
 * 1460 WHEN USING CAMDENTON ALTIMETER SETTING.
 CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.
 CHART NOTE: PROCEDURE NA AT NIGHT.
 (SEE FORM 8260-10)

QUALITY
1
CHECKED

CITY AND STATE OSAGE BEACH, MO	ELEVATION: 876 AIRPORT NAME: GRAND GLAIZE- OSAGE BEACH	THRE: 858 FACILITY IDENTIFIER: SHY	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 32, AMDT 6 05/02/13	SUP
				AMDT 5
				DATE 04/18/2002

VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: USE KAISER LAKE OZARK ALTIMETER SETTING; WHEN NOT RECEIVED, USE CAMDENTON ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET.

QUALITY
1
CHECKED

CITY AND STATE
OSAGE BEACH, MO

ELEVATION: 876 THRE: 858
AIRPORT NAME:
GRAND GLAIZE- OSAGE BEACH

FACILITY
IDENTIFIER:
SHY

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
VOR RWY 32, AMDT 6
05/02/13

SUP:
AMDT: 5
DATED: 04/18/2002