

U.S. Department of Transportation  
Federal Aviation Administration

**RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
LOFTY (40E)	FIMEN (TF)(FB)(40E)(43A)	285.10/17.99	2700	LNAV: RW04 CLIMB TO 2700 DIRECT RACOD AND HOLD.
SEXTN (40E)	CITIX (TF)(FB)(40E)(43A)	140.92/11.37	2700	
CITIX (IAF)(40E)(43A)	JANGI (NOPT)(TF)(FB)(40E)(41E)(43B)	131.84/5.00	2700	ADDITIONAL FLIGHT DATA: HOLD NE, RT, 222.12 INBOUND FAS OBST: 960 TOWER 394305N/0901758W GELBE TO RW04: 3.05/40 CHART VDP AT 1.74 MILES TO RW04 CHART: PRUITT A AND B MOA ROUTE TYPE DESCRIPTION: A, P APPROACH ROUTE QUALIFIER 2: S
FIMEN (IAF)(40E)(43A)	JANGI (NOPT)(TF)(FB)(40E)(41E)(43B)	311.94/5.00	2700	
JANGI (IF/IAF)(40E)(43I)	GELBE (TF)(FB)(40E)(43F)	041.89/6.42	2300	
RW04 (MAP)(40G)(41Y)(43M)	1024 MSL (CA)(42M)	041.95		
1024 MSL	RACOD (DF)(FO)(40E)(41E)(43H)		2700	

- PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
- HOLD SW JANGI, RT, 041.89 INBOUND, 2700 FT IN LIEU OF PT (IAF)(40E)(41E)(43C)
- FAC: 041.95 FAF: GELBE DIST FAF TO MAP: 5.08 THLD: 5.08
- MIN. ALT: JANGI 2700, GELBE 2300
- DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
- MIN GS INCPT:        GS ALT AT:        OM:        MM:        IM:
- GS ANGLE:        TCH: 34:1 IS CLEAR
- MSA FROM: RW04 2700

MAG VAR: 3E                      EPOCH YEAR: 80

**MINIMUMS**

TAKEOFF:	X	STANDARD	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD#										
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1220	1	600	1220	1	600	1220	1 1/2	600	1220	1 3/4	600			
CIRCLING	1220	1	596	1220	1	596	1220	1 1/2	596	1220	2	596			

NOTES: CHART NOTES: DME/DME RNP-0.3 NA. PROCEDURE NA AT NIGHT. IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE SPRINGFIELD, IL ALTIMETER SETTING AND INCREASE ALL MDAs 80 FEET. VDP NA WITH SPRINGFIELD, IL ALTIMETER SETTING. #NA WHEN LOCAL WEATHER NOT AVAILABLE.  
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL AT SEXTN VIA V580 NORTHBOUND AND VIA V50 WESTBOUND.

CITY AND STATE  JACKSONVILLE, IL	ELEVATION: 624 TDZE: 620	FACILITY IDENTIFIER:  RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: OCT 27 2005 RNAV (GPS) RWY 4, ORIG	SUP:
	AIRPORT NAME: JACKSONVILLE MUNI			AMDT: NONE
				DATE