

U.S. Department of Transportation
Federal Aviation Administration

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
AVUYA WP (IAF)	FERES WP (TF) (FB) (NoPT)	088.45/5.00	3000	LNAV: RW36
ECEBA WP (IAF)	FERES WP (TF) (FB) (NoPT)	266.57/5.00	3000	CLIMB TO 2500 DIRECT CERBU WP AND HOLD
FERES WP (IF/IAF)	HEPEX WP (TF) (FB)	356.52/6.00	2000	
RW36 (MAP)	820 MSL (CA)	356.52		
820 MSL	CERBU WP (DF) (FO)		2500	ADDITIONAL FLIGHT DATA: HOLD N, RT, 176.52 INBOUND FAS OBST: 555 TOWER 314648/0954256

- PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD S OF FERES WP, RT, 356.52 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 356.52 FAF: HEPEX WP DIST FAF TO MAP: 4.80 THLD: 4.80
- MIN. ALT: FERES WP 3000, HEPEX WP 2000
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS CLEAR
- MSA FROM:

CHART VDP AT 1.15NM TO RW36
HEPEX WP TO RW36: 3.04/40
FINAL SEGMENT (TF)
CHART: AIRPORT ELEV 423
TDZE 415
MAG VAR: 4E EPOCH YEAR: 05

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	X											
CATEGORY	A			B			C			D			E			
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	
LNAV MDA	820	1	405	820	1	405	820	1 1/4	405	820	1 1/4	405				
CIRCLING	860	1	437	1040	1	617	1040	1 3/4	617	1060	2	637				

NOTES:
VDP NA WITH C. DAVID CAMPBELL FIELD-CORSICANA MUNI ALTIMETER SETTING
GPS OR RNP-0.3 REQUIRED. DME/DME RNP -0.3 NA.
IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE C. DAVID CAMPBELL FIELD-CORSICANA MUNI ALTIMETER SETTING AND INCREASE ALL MDA'S 100 FEET.

CITY AND STATE PALESTINE, TX	ELEVATION: 423 TDZE: 415 AIRPORT NAME: PALESTINE MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 36, AMDT 1 SEP 30 2004	SUP: AMDT: ORIG-A DATE: 04/17/03
--	--	-------------------------------------	--	--

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV

STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA:

FROM	TO	ALTITUDE
1. 267/30 CW 086/30	FERES WP (IF/IAF) (NoPT)	3000
2. 086/30 CW 177/30	AVUYA WP (IAF)	3000
3. 177/30 CW 267/30	ECEBA WP (IAF)	3000

CITY AND STATE

PALESTINE, TX

ELEVATION:

423 TDZE:

415

AIRPORT NAME:

PALESTINE MUNI

FACILITY IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

SEP 30 2004
RNAV (GPS) RWY 36, AMDT 1

SUP:

AMDT: ORIG-A

DATED: 04/17/03