

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)
TITLE 14 CFR PART 97.37**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>AIRPORT</u>	<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>	<u>AMDT NO</u>	<u>ACTUAL EFFECTIVE DATE</u>
THOMASTON-UPSON COUNTY	KOPN	THOMASTON	GA	2A	12 AUGUST 2021

TAKEOFF MINIMUMS:

RWY 12: STANDARD.

RWY 30: STANDARD WITH MINIMUM CLIMB OF 268 FT PER NM TO 1800, OR 1100-3 FOR VCOA.

TEXTUAL DEPARTURE PROCEDURES:

VISUAL CLIMB OVER AIRPORT:

RWY 30: OBTAIN ATC APPROVAL FOR VCOA WHEN REQUESTING IFR CLEARANCE. CLIMB IN VISUAL CONDITIONS TO CROSS THOMASTON-UPSON COUNTY AIRPORT OR ABOVE 1700 BEFORE PROCEEDING ON COURSE.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 12: TREE 2885 FT FROM DER, 510 FT LEFT OF CENTERLINE, 885 FT MSL. TREE 3280 FT FROM DER, 1067 FT LEFT OF CENTERLINE, 894 FT MSL.

NOTE: RWY 30: TREES BEGINNING 801 FT FROM DER, 444 FT RIGHT OF CENTERLINE, UP TO 866 FT MSL. TREE 969 FT FROM DER, 601 FT RIGHT OF CENTERLINE, 867 FT MSL. TRANSMISSION LINE AND CATENARY BEGINNING 1625 FT FROM DER, 274 FT LEFT OF CENTERLINE, UP TO 105 FT AGL/863 FT MSL.

CONTROLLING OBSTACLES:

RWY 30: 1556 FT MSL TOWER 325946.00N/0842005.00W

VISUAL CLIMB AREA OBSTACLE: 1556 FT MSL TOWER 325946.00N/0842005.00W, 949 FT MSL TREE 325749.00N/0841451.00W



REMARKS:

FLIGHT INSPECTED BY

PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJF-10) MEMO, APRIL 29, 2020 SUBJECT: FLIGHT INSPECTION REVIEW NOT REQUIRED.

OFFICE

DATE

DEVELOPED BY

DONALD LANIER (CHRISTOPHER SCHONES)

Digitally signed by
DONALD H LANIER
Mar 04, 2021

Digitally signed by
DONALD H LANIER
Mar 04, 2021

OFFICE

AJV-A431

DATE

02/09/2021

APPROVED BY

LONNIE EVERHART

Digitally signed by
DONALD H LANIER
Mar 04, 2021

OFFICE

AJV-A430

DATE

TITLE

MANAGER

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:

A4A ☐ **ALPA** ☒ **AOPA** ☒ **APA** ☐ **HAI** ☐ **NBAA** ☒ **OTHER:** ZTL, AMGR, EASTERN FPT

CHANGES - REASONS:

1. CHANGED TAKEOFF MINIMUM VCOA VISIBILITY FROM "2 1/2 SM" TO "3 SM" - MEET CURRENT CRITERIA.
2. REMOVED VCOA INSTRUCTIONS FROM TEXTUAL DEPARTURE PROCEDURE BLOCK AND RELOCATED THEM IN VCOA BLOCK - NEW 8260-15A FORM AND IAW 8260.46G.
3. ADDED "OBTAIN ATC APPROVAL FOR VCOA WHEN REQUESTING IFR CLEARANCE" TO VISUAL CLIMB OVER AIRPORT SECTION - IAW 8260.46G.
4. UPDATED TAKEOFF OBSTACLE NOTES FOR RWYS 12 AND 30 - NEW EVALUATION IN DEPARTURE OBSTACLE GROUPER.

