

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> JBR	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 31	<u>ORIGINAL/AMENDMENT</u> 1D	<u>CITY</u> JONESBORO	<u>STATE</u> AR
<u>AIRPORT ELEVATION</u> 262	<u>TDZE</u> 258	<u>SUPERSEDED</u> RNAV (GPS) RWY 31	<u>DATED</u> 03/25/2021	<u>MAG VAR</u> 0W
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 2 OCTOBER 2025	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>EPOCH YEAR</u> 2015
			<u>CANCEL/SUSPEND</u>	

TAA

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>ALTITUDE</u>
1. 225/30 CW 045/30	NOPT	SUBSE	IF/IAF	2500
2. 045/30 CW 225/30		SUBSE	IF/IAF	3100

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
SUBSE	IF/IAF	COYMC		TF	FB	1.00	314.73	7.00	2200
COYMC	FAF	POVIC/2.90 NM TO RW31		TF	FB	0.30	314.67	3.08	
POVIC/2.90 NM TO RW31		RW31	MAP	TF	FO	0.30	314.67	2.90	
RW31	MAP	800 MSL		CA			314.67		800
800 MSL		YIGUY		DF	FO	1.00			2300

MISSED APPROACH

MAP:

LP: RW31
LNAV: RW31

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 800 THEN CLIMBING LEFT TURN TO 2300 DIRECT YIGUY AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

- PT
- SIDE OF COURSE
- OUTBOUND
- FT WITHIN
- MILES OF (IAF)
- HOLD SE SUBSE, RT, 314.73 INBOUND, 2500 IN LIEU OF PT (IAF), MAX 6000.
- FAC: 314.67 FAF: COYMC DIST FAF TO MAP: 5.98 DIST FAF TO THLD: 5.98
- MIN ALT: SUBSE 2500, COYMC 2200, POVIC/2.90 NM TO RW31 1220
- DIST TO THLD FROM OM: MM: IM: 150 HAT: GS ANT: MM: IM:
- MIN GP INCPT: GP ALT AT FAF:
- GP ANGLE: 34:1 IS NOT CLEAR 20:1 IS NOT CLEAR TCH:
- MSA FROM:



PBN REQUIREMENTS NOTE:

RNP APCH - GPS

NOTES:

CHART NOTE: RWY 31 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.
CHART NOTE: CIRCLING NA NW OF RWY 5-23.
CHART NOTE: PROCEDURE NA AT NIGHT.
CHART NOTE: CIRCLING RWY 13 NA.

ADDITIONAL FLIGHT DATA:

HOLD SW, RT, 050.11 INBOUND.
CHART FAS OBST: 386 ANTENNA (05-115006) 354838N/0903750W.
CHART 499 TOWER (05-001532) 354510N/0903425W.
WAAS CHANNEL # 50531
REFERENCE PATH ID: W31A
COYMC TO RW31: 3.00/45.
LTP HAE: 48.8 M

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ STANDARD - CAT D 900-2 3/4, NA WHEN LOCAL WEATHER NOT AVAILABLE.

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LP MDA	640	1	382	640	1	382	640	1 1/8	382	640	1 1/8	382			
LNAV MDA	640	1	382	640	1	382	640	1 1/8	382	640	1 1/8	382			
CIRCLING	740	1	478	740	1	478	820	1 1/2	558	1080	2 3/4	818			

CHANGES - REASONS

1. RAISED LP HAT/MDA MINIMUMS FROM "600/342" TO "640/382". - NEW TARGETS EVAL/NEW OBSTACLES.
2. INCREASED LP CAT C/D VISIBILITY MINIMUMS FROM "1" TO "1 1/8" SM. - NEW TARGETS EVAL/NEW OBSTACLES.
3. CHART NOTE CHANGED FROM " WHEN LOCAL ALTIMETER NOT RECEIVED, USE WALNUT RIDGE ALTIMETER SETTING: INCREASE ALL MDAS 60 FEET AND LP CAT C/D VISIBILITY 1/8 SM AND LNAV CAT C/D AND CIRCLING CAT C 1/4 SM" TO "WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ARG ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET AND VISIBILITY CAT C/D 1/4 SM". AND MOVED TO REMARKS IN THE -9. - NEW CRITERIA.



COORDINATED WITH:

A4A

☒

ALPA

☒

AOPA

☒

APA

☐

HAI

☐

NBAA

☒

OTHER: ZME, AMGR, JBR FSS

FLIGHT CHECKED BY RUSSELL ROSLEWSKI	Digitally signed by ALLAN WILL Jul 14, 2025 Digitally signed by ALLAN WILL Jul 14, 2025 Digitally signed by ALLAN WILL Jul 14, 2025	OFFICE AJF OFFICE AJV-33 OFFICE AJV-33	DATE 07/08/2025 DATE 05/01/2025 DATE 05/01/2025	TITLE MANAGER
---	--	--	---	-------------------------------------

FAS DATA BLOCK INFORMATION

DATA FIELD OPERATION TYPE SBAS SERVICE PROVIDER IDENTIFIER AIRPORT IDENTIFIER RUNWAY APPROACH PERFORMANCE DESIGNATOR ROUTE INDICATOR REFERENCE PATH DATA SELECTOR REFERENCE PATH IDENTIFIER (APPROACH ID) LTP/FTP LATITUDE LTP/FTP LONGITUDE LTP/FTP ELLIPSOIDAL HEIGHT FPAP LATITUDE FPAP LONGITUDE THRESHOLD CROSSING HEIGHT (TCH) TCH UNITS SELECTOR (METERS OR FEET USED) GLIDEPATH ANGLE (GPA) COURSE WIDTH AT THRESHOLD LENGTH OFFSET HORIZONTAL ALERT LIMIT (HAL) VERTICAL ALERT LIMIT (VAL) CRC REMAINDER	DATA 0 0 KJBR RW31 0 0 W31A 354926.0550N 0903846.9265W +00488 355028.7300N 0904004.9300W 00045.0 F 03.00 106.75 1504 40.0 00.0 0055F235
---	--

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE LTP ORTHOMETRIC HEIGHT FPAP ORTHOMETRIC HEIGHT	K4 +00767 +00767
---	---

