

**Federal Aviation
Administration**

Transmittal Letter 20-04

December 27, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
1/30/2020	FL	Orlando	Orlando Sanford Intl	9/5078	12/16/2019	ILS OR LOC RWY 9R, Amdt 1A

AIRAC Date: 30 JANUARY 2020

FDC 9/5078 SFB IAP ORLANDO SANFORD INTL, ORLANDO, FL. ILS OR LOC RWY 9R, AMDT 1A... S-ILS 9R DA 239. S-LOC 9R HAT 501 ALL CATS. JOSKA FIX MINIMUMS: S-LOC 9R HAT 401 ALL CATS. CHART CIRCLING ICON. CIRCLING CAT C MDA 600/HAA 545, CAT D MDA 640/HAA 585. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE EXECUTIVE ALTIMETER SETTING AND INCREASE DA 43 FEET AND ALL MDA 60 FEET; INCREASE S-LOC 9R CATS C/D VISIBILITY 1/4 MILE, CIRCLING CAT C VISIBILITY 1/8 MILE, AND JOSKA FIX MINIMUMS S-LOC 9R CAT C/D VISIBILITY 1/4 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE EXECUTIVE ALTIMETER SETTING AND INCREASE S-ILS DA TO 282, AND ALL MDA 60 FEET; INCREASE S-LOC 9R CAT C,D VISIBILITY 1/4 MILE, CIRCLING CAT C VISIBILITY 1/8 MILE, AND JOSKA FIX MINIMUMS S-LOC 9R CATS C,D VISIBILITY 1/4 MILE. DELETE TDZE 47. CHART TDZE 39. THIS IS ILS OR LOC RWY 9R, AMDT 1B. 1912101601-PERM