

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
 NDB STANDARD INSTRUMENT APPROACH PROCEDURE  
 FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: BHC NDB
				CLIMB TO 1600 THEN CLIMBING RIGHT TURN TO 2000 DIRECT BHC NDB AND HOLD.
				<b>ADDITIONAL FLIGHT DATA:</b> HOLD SE, RT, 301.88 INBOUND. FAS OBST: 445 AAO 314250N/0822338W CHART: MAX 6000 AT BHC NDB. FAC CROSSES RWY C/L EXTENDED 3002 FROM THLD.

1. PT L SIDE OF COURSE 269.14 OUTBOUND 2000 FT WITHIN 10 MILES OF BHC NDB (IAF)  
 2. \_\_\_\_\_  
 3. FAC 089.14 FAF \_\_\_\_\_ DIST FAF TO MAP \_\_\_\_\_ THLD \_\_\_\_\_  
 4. MIN. ALT \_\_\_\_\_  
 8. MSA FROM: BHC NDB 2300

MAG VAR: 6W                      EPOCH YEAR: 2010

MINIMUMS																
TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N		A		X					
CATEGORY =====>	A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-8	800	1	599	800	1	599	800	1 3/4	599	800	1 3/4	599				
CIRCLING	800	1	599	800	1	599	800	1 3/4	599	800	2	599				

**NOTES:**  
 CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 08 PROCEDURE NA AT NIGHT.  
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.  
 CHART PLANVIEW NOTE: RADAR REQUIRED.  
 CHART NOTE: WHEN VGSI INOP, CIRCLING TO RWY 26 NA AT NIGHT.  
 (SEE FORM 8260-10)



CITY AND STATE BAXLEY, GA	ELEVATION: 201                      THRE: 201 AIRPORT NAME:  BAXLEY MUNI	FACILITY IDENTIFIER: BHC	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 8, AMDT 2  31 MAY 2012	SUP AMDT 1A DATE 05/22/2008
------------------------------	---	-----------------------------	--	-----------------------------------

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**NOTES, (CONT.):**

**CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ALMA ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET.**



CITY AND STATE <b>BAXLEY, GA</b>	ELEVATION: 201      THRE: 201 AIRPORT NAME: <b>BAXLEY MUNI</b>	FACILITY IDENTIFIER: <b>BHC</b>	PROCEDURE NO./AMDT NO.,EFFECTIVE DATE: <b>NDB RWY 8, AMDT 2</b> <b>31 MAY 2012</b>	SUP:
				AMDT: <b>1A</b>
				DATED: <b>05/22/2008</b>