

**Federal Aviation
Administration**

Transmittal Letter 20-13

May 1, 2020

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
6/18/2020	FL	Fort Pierce	Treasure Coast Intl	0/2808	4/14/2020	RNAV (GPS) RWY 28L, Amdt 1B

AIRAC Date: 18 JUNE 2020

FDC 0/2808 FPR IAP TREASURE COAST INTL, FORT PIERCE, FL. RNAV (GPS) RWY 28L, AMDT 1B...
CHART CIRCLING ICON. CIRCLING CAT C MDA 880/ HAA 857, CAT D MDA 880/ HAA 857, VISIBILITY
CAT C 2 1/2 SM, CAT D 2 3/4 SM. DELETE CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT
RECEIVED, USE VERO BEACH ALTIMETER SETTING AND INCREASE LNAV/VNAV DA 24 FEET AND
ALL MDA 40 FEET; INCREASE LNAV/VNAV ALL CATS AND LNAV ALL CATS C/D VISIBILITY 1/8 MILE.
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE VERO BEACH ALTIMETER
SETTING AND INCREASE LNAV/VNAV DA TO 435 FEET AND MDA 40 FT; INCREASE LNAV/VNAV
VISIBILITY ALL CATS AND LNAV VISIBILITY CATS C/D 1/8 SM. INCREASE CIRCLING VISIBILITY CAT
C/D 1/4 SM. ALTERNATE MINIMUMS: STANDARD, EXCEPT CAT C 900 2 1/2 AND CAT D 900 2 3/4 SM.
NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 28L, AMDT 1C. 2004021758-
PERM