#### FEDERAL AVIATION ADMINISTRATION

# FLIGHT STANDARDS SERVICE ILS STANDARD INSTRUMENT APPROACH PROCEDURE

#### TITLE 14 CFR PART 97.29

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.

Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

AIRPORT AIRPORT ID PROCEDURE NAME ORIGINAL/AMENDMENT CITY STATE
HUNTSVILLE INTL-CARL T JONES FIELD KHSV ILS OR LOC RWY 36L 11B HUNTSVILLE AL

 AIRPORT ELEVATION
 TDZE
 SUPERSEDED
 ORIGINAL/AMENDMENT
 DATED
 MAG VAR
 EPOCH YEAR

 629
 615
 ILS OR LOC RWY 36L
 11A
 08/15/2019
 4W
 2020

FACILITY COORDINATES OF FACILITIES ACTUAL EFFECTIVE DATE REQUIRED EFFECTIVE DATE CANCEL/SUSPEND

1-ELL ROUTINE

CANCEL/SUSPEND

ROUTINE

#### **TERMINAL ROUTES**

FROM	FIX TYPE	<u>TO</u>	FIX TYPE	LEG TYPE	FO/FB	RNP	<u>COURSE</u>	DISTANCE	ALTITUDE
BOSAC INT/RADAR	IF/IAF	CECAB/RADAR					004.95	5.88 (I-ELL)	2800

#### MISSED APPROACH

# MAP:

ILS: DA LOC: 6.71 NM AFTER CECAB/RADAR

# MISSED APPROACH INSTRUCTIONS:

CLIMB TO 1100 THEN CLIMBING LEFT TURN TO 3000 ON HEADING 350 AND RQZ R-261 TO TANNE INT/RQZ 17.61 DME AND HOLD.

## ALTERNATE MISSED APPROACH INSTRUCTIONS:

#### PROFILE:

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)

2. HOLD S BOSAC, LT. 004.95 INBOUND, 2800 FT, IN LIEU OF PT (IAF), MAX 5000.

**3. FAC:** 004.95 **FAF:** CECAB/RADAR **DIST FAF TO MAP:** 6.71 **DIST FAF TO THLD:** 6.71

4. MIN ALT: BOSAC INT/RADAR 2800, CECAB/RADAR 2800

5. DIST TO THLD FROM OM: MM: IM: 150 HAT: GS ANT: 1000

6. MIN GS INCPT: 2800 GS ALT AT FAF: CECAB/RADAR 2800 OM: MM: IM:

**7. GP ANGLE**: 3.00 **34:1**: **20:1**: TCH: 53.4

8. MSA FROM: RQZ VORTAC 3700

## **EQUIPMENT REQUIREMENTS NOTES:**

RADAR REQUIRED FOR PROCEDURE ENTRY.

AIRPORT AIRPORT ID PROCEDURE NAME ORIGINAL/AMENDMENT CITY STATE
HUNTSVILLE INTL-CARL T JONES FIELD KHSV ILS OR LOC RWY 36L 11B HUNTSVILLE AL

# NOTES:

CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED.

CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-ILS 36L CAT E VISIBILITY TO RVR 4000, S-LOC 36L CAT C/D/E VISIBILITY TO 1 3/4 SM.

CHART NOTE: CIRCLING NA FOR CAT C/D/E E OF RWY 18L-36R.

CHART PLANVIEW NOTE: CAUTION NUMEROUS MIGRATORY BIRD FLOCKS IN AREA. WILDLIFE REFUGE AREA SOUTH OF AIRPORT.

## **ADDITIONAL FLIGHT DATA:**

CHART NOTE: ASR.
CHART CIRCLING ICON.
CHART WHEELER NATIONAL WILDLIFE REFUGE
CHART R2104A, R2104B, R2104C
FAS OBST: 960 AAO 343160N/0864637W.
990 AAO 343018N/0864748W.
HOLD W, RT, 080.97 INBOUND

## MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ILS: STANDARD - NA WHEN LOCAL WEATHER NOT AVAILABLE., NA WHEN CONTROL TOWER CLOSED.; LOC: STANDARD - CAT E 800-2 1/4, NA WHEN LOCAL WEATHER NOT AVAILABLE., NA WHEN CONTROL TOWER CLOSED.

CATEGORY:		Α			В			С			D			E	
FINAL TYPE	DA/MDA	<u>VIS</u>	HAT/HAA	<u>DA/MDA</u>	<u>VIS</u>	HAT/HAA	<u>DA/MDA</u>	<u>VIS</u>	HAT/HAA	DA/MDA	<u>VIS</u>	HAT/HAA	DA/MDA	<u>VIS</u>	HAT/HAA
S-ILS 36L	815	1800	200	815	1800	200	815	1800	200	815	1800	200	815	1800	200
S-LOC 36L	1240	2400	625	1240	2400	625	1240	1 3/8	625	1240	1 3/8	625	1240	1 3/8	625
CIRCLING	1240	1	611	1240	1	611	1240	1 3/4	611	1240	2	611	1260	2 1/4	631

#### **CHANGES - REASONS**

#### **COORDINATED WITH:**

A4A X ALPA X	AOPA X APA X	HAI NBAA X	OTHER: ZME, HSV APCH CON, HSV ATCT, S	ST AERO, AMGR	
FLIGHT CHECKED BY ROBERT E WILLIAMS	Digitally signed by <b>DAVID DANNER</b> Jan 22, 2020		OFFICE FICO	<b>DATE</b> 1/16/20	
DEVELOPED BY	04.1,0	Digitally signed by  RALPH DUMAR	<u>OFFICE</u> AJV-A422	<u>DATE</u> 11/27/2019	
RALPH DUMAR	Digitally signed by	Dec 20, 2019	OFFICE	DATE	TITLE
APPROVED BY MARLON ROBINSON	DAVID DANNER Jan 22, 2020		AJV-A420	<u> </u>	MANAGER

ONALITY CHECKER

<sup>1.</sup> CHANGED DISTANCE BETWEEN IF BOSAC AND FAF CECAB FROM 6.00 TO 5.88 NM - FAF RELOCATED IN AMDT 11 WITHOUT CORRESPONDING ADJUSTMENTS TO DISTANCES BETWEEN IF AND FAF AND BETWEEN FAF AND MAP. FAF TO MAP DISTANCE CORRECTED IN AMDT 11A.

<sup>2.</sup> ADDED 'NA WHEN LOCAL WEATHER NOT AVAILABLE' TO ILS AND LOC ALTERNATE MINIMUMS - NOTE REQUIRED REGARDLESS OF WHETHER OR NOT A PROCEDURE HAS A BACKUP ALTIMETER, PER 8260.19H CHANGE 1 IMPLEMENTATION LETTER (AFS CLARIFICATION).