

**Federal Aviation
Administration**

Transmittal Letter 23-19

July 21, 2023

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
9/7/2023	OH	Wapakoneta	Neil Armstrong	3/5614	6/23/2023	RNAV (GPS) RWY 26, Orig-B

AIRAC Date: 7 SEPTEMBER 2023

FDC 3/5614 AXV IAP NEIL ARMSTRONG, WAPAKONETA, OH. RNAV (GPS) RWY 26, ORIG-B... CHANGE PBN REQUIREMENTS NOTE TO READ: RNP APCH - GPS. DELETE NOTE: VDP NA WHEN USING LIMA ALTIMETER SETTING. DELETE PROFILE NOTE ASTERISK LNAV ONLY. DELETE VDP 1.5 NM TO RW26. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LIMA ALTIMETER SETTING AND INCREASE LPV DA TO 1291 FEET AND ALL VISIBILITIES 1/8 SM. INCREASE LNAV/VNAV DA TO 1324 FEET AND ALL VISIBILITIES 1/8 SM. INCREASE ALL MDAS 60 FEET AND LNAV VISIBILITY CAT C 1/4 SM. APT ELEV 912. CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. THIS IS RNAV (GPS) RWY 26, ORIG-C. 2306231751-PERM